

| <b>TESTREPORT</b>  |  |
|--|--|
| <b>Grid-connected Inverter Regulation of<br/>Provincial Electricity Authority(PEA)</b> |  |
| <b>Report Number</b> .....   | ES190702001P   |
| <b>Date of issue</b> .....   | July 30. 2019  |
| <b>Total number of pages</b> .....   | 48 pages   |
| <b>Testing Laboratory Name</b> .....   | EMTEK (SHENZHEN) CO., LTD.   |
| <b>Address</b> .....   | Bldg 69. Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China   |
| <b>Applicant's name</b> .....  | Shenzhen ATESS Power Technology Co.,Ltd  |
| <b>Address</b> .....   | 1st Floor of Building 3 at Sector B and 3rd Floor of Building 9, Henglong Industrial Park, No.4 Industrial Zone, Shuitian Community, Shiyan Street, Baoan District, Shenzhen |
| <b>Test specification:</b>   |  |
| <b>Standard</b> .....  | IEC 61727-2004. IEC 62116-2014   |
| <b>Non-standard test method</b> .....  | N/A  |
| <b>Test item description</b> .....   | Hybrid Power systems   |
| <b>Trade mark</b> .....  |   |
| <b>Reference</b> .....   | N/A  |
| <b>Number</b> .....  | HPS120   |
| <b>Firmware version</b> .....  | T11.0  |
| <b>Date of receipt of test item</b> .....  | July 03. 2019  |
| <b>Date(s) of performance of test</b> .....  | July 03. 2019 to July 29. 2019   |
| <b>Date of report issue</b> .....  | July 30. 2019  |

Tested by

*Tom Tao*

(Mr. Tom Tao)  
Testing Engineer  
( 2019-07-30)

Review by

*Double Lee*

(Mr. Double Lee)  
Project Engineer  
(2019-07-30)

Approved by



(Mr. Paulin Hu)  
Department Manager  
(2019-07-30)

Summary of testing

Test result of PV Grid-tied inverter model HPS120, It was tested by SHENZHEN EMTEK CO., LTD and complied according to requirements on grid connection of Provincial Electricity Authority (PEA) as following

| Clause | Item                                | Standard method | Result |
|--------|-------------------------------------|-----------------|--------|
| 1      | Harmonics                           | IEC 61000-3-2   | PASS   |
| 2      | Voltage Fluctuation                 | IEC 61000-3-5   | PASS   |
| 3      | Direct Current Injection            | IEC 61727       | PASS   |
| 4      | Reactive Power Control              | PEA             | PASS   |
| 5      | Active Power Control                | PEA             | PASS   |
| 6      | Low Voltage Fault Ride Through      | PEA             | PASS   |
| 7      | Under and Over Voltage Protection   | IEC 61727       | PASS   |
| 8      | Under and Over Frequency Protection | IEC 61727       | PASS   |
| 9      | Anti-Islanding                      | IEC 62116       | PASS   |
| 10     | Response to Utility Recovery        | IEC 61727       | PASS   |

Copy of marking plate:

| <b>ATESS</b><br>Hybrid Power Systems  |  |
|---|--|
| <b>Model</b>  | <b>HPS120</b>  |
| PV Max generating power   | 180kW  |
| Max PV Open-circuit voltage   | 1000Vdc  |
| PV MPPT voltage range   | 480-800Vdc   |
| Battery voltage range   | 352-600Vdc   |
| Battery Max charge/discharge power  | 180kW/132kW  |
| AC Rated voltage  | 400Vac   |
| AC Rated frequency  | 50/60Hz  |
| AC Rated current  | 173A   |
| AC Rated output power   | 120kW  |
| Max AC output power   | 132kVA   |
| Max Bypass power  | 240kVA   |
| PF Range  | 0.8lagging--0.8leading   |
| Ingress Protection  | IP20   |
| Communication Port  | RS485/CAN  |
| Operating Temp.Range  | -25°C to +55°C   |
| <b>DATE OF MADE</b>   |  |
| <b>S/N:</b>   |  |
|   | <b>S / N: T0 D0 A0 8 0 1 4</b>   |
|  | <a href="http://www.atepower.com">www.atepower.com</a><br>MADE IN CHINA              |



| GRID-CONNECTED INVERTER REGULATION OF PROVINCIAL ELECTRICITY AUTHORITY (PEA) |   |                 |         |
|--|---|-----------------|---------|
| Clause   | Requirement – Test  | Result – Remark | Verdict |
| 1  | Harmonics   |                 | P       |
|  | The power generating system of VSPP must not inject harmonic current to the grid system exceeding the limit based on the PEA's rules concerning the Regulations of Grid Connection B.E.2559. In terms of verification at other levels of voltage beyond the aforementioned requirements, the appropriate standard of IEC must be applied. | See table 1     | P       |
| 2  | Voltage Fluctuation   |                 | P       |
|  | The power generating system of VSPP must not create voltage fluctuation exceeding the limit based on the PEA's rules concerning the Regulations on Grid Connection B.E.2559.  |                 | P       |
|  | Inverters shall not cause voltage fluctuation beyond the limits defined by the IEC 61000-3-3 (2008) for inverters with rated current $\leq 16$ A  |                 | N       |
|  | IEC 61000-3-5 (2009) for inverters with rated currents greater than 75 A or   | See table 2     | P       |
|  | IEC 61000-3-11 (2000) for inverters with rated currents $\leq 75$ A.  |                 | N       |
| 3  | Direct Current Injection  |                 | P       |
|  | The power generating system of VSPP must not supply direct current to the grid system exceeding the limit based on the PEA's regulations concerning the Regulations on Grid Connection B.E.2559.  | See table 3     | P       |
| 4  | Reactive Power Control  |                 | P       |
|  | The power generating system of VSPP must be able to control power factor (PF) or reactive power to maintain voltage level at PCC aligned with PEA's standards. The power generating system of service applicants must have capacity as stated in Table 1.   | See table 4     | P       |
| 4.1  | Voltage Level at PCC is Low voltage<br>Capacity in Adjusting Power Factor at 0.95 lagging to 0.95 leading as a minimum<br>Reactive Power Control Methods: At least one method can control which is a fixed displacement factor $\cos \theta$  | See table 4.1   | P       |
| 4.2  | Voltage Level at PCC is moderate voltage or high voltage (electrical installation not exceeding 500 kilowatt).<br>Capacity in Adjusting Power Factor at 0.95 lagging to 0.95 leading as a minimum<br>Reactive Power Control Methods: At least one method can control which is a fixed displacement factor $\cos \theta$                   |                 | N       |

| GRID-CONNECTED INVERTER REGULATION OF PROVINCIAL ELECTRICITY AUTHORITY (PEA)                              |   |                 |                        |   |              |  |                        |             |   |
|---|---|-----------------|------------------------|---|--------------|--|------------------------|-------------|---|
| Clause  | Requirement – Test  | Result – Remark | Verdict                |   |              |  |                        |             |   |
| 4.3   | Voltage Level at PCC is Moderate voltage or high voltage (electrical installation exceeding 500 kilowatt).<br>Capacity in Adjusting Power Factor at 0.90 lagging to 0.90 leading as a minimum   |                 | N                      |   |              |  |                        |             |   |
|   | Reactive Power Control Methods: can control which a fixed displacement factor $\cos \theta$   |                 | N                      |   |              |  |                        |             |   |
|   | Reactive Power Control Methods: can control which a variable reactive power depending on the voltage Q(U)   |                 | N                      |   |              |  |                        |             |   |
| 5   | Active Power Control  |                 | P                      |   |              |  |                        |             |   |
|   | The power generating system of VSPP must be capable of reducing electric power from 100% to zero by decreasing 10% electric power per one minute. In this regard, if there is any abnormality occurred in the grid system or any incident considered by PEA as an impact affecting safety and stability of the grid system, PEA would inform and/or give an order to the VSPP to reduce electric power as appropriate.  | See table 5     | P                      |   |              |  |                        |             |   |
| 6   | Low Voltage Fault Ride Through  |                 | P                      |   |              |  |                        |             |   |
|   | <p>The power system of VSPP must not disconnect itself from the grid system within the required period during temporary low voltage of the grid system. The voltage at PCC is determined as shown in Table 2.</p> <p>Table 2. Duration of Low Voltage Fault Ride Through</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Voltage at PCC</th> <th style="width: 50%;">Duration Time (Second)</th> </tr> </thead> <tbody> <tr> <td>1) Low voltage<br/>2) Moderate voltage or high voltage (electrical installation not exceeding 500kilowatt)</td> <td>Not required</td> </tr> <tr> <td>3) Moderate voltage or high voltage (electrical installation exceeding 500kilowatt).</td> <td>As shown in Picture 1.</td> </tr> </tbody> </table> | Voltage at PCC  | Duration Time (Second) | 1) Low voltage<br>2) Moderate voltage or high voltage (electrical installation not exceeding 500kilowatt) | Not required | 3) Moderate voltage or high voltage (electrical installation exceeding 500kilowatt). | As shown in Picture 1. | See table 6 | P |
| Voltage at PCC  | Duration Time (Second)  |                 |                        |   |              |  |                        |             |   |
| 1) Low voltage<br>2) Moderate voltage or high voltage (electrical installation not exceeding 500kilowatt) | Not required  |                 |                        |   |              |  |                        |             |   |
| 3) Moderate voltage or high voltage (electrical installation exceeding 500kilowatt).                      | As shown in Picture 1.  |                 |                        |   |              |  |                        |             |   |
| 7   | Under and Over Voltage Protection   |                 | P                      |   |              |  |                        |             |   |

| GRID-CONNECTED INVERTER REGULATION OF PROVINCIAL ELECTRICITY AUTHORITY (PEA) |  |                 |         |
|--|--|-----------------|---------|
| Clause   | Requirement – Test   | Result – Remark | Verdict |
|  | <p>The power system of VSPP must disconnect itself from the grid system if voltage level of line to neutral in the utility system is out of ranges as stated in Table 3</p> <p>Table 3. The Disconnect Duration of Falling Voltage Out of Rated Voltage Ranges</p>   | see table 7     | P       |
| 8  | Under and Over Frequency Protection  |                 | P       |
|  | The power generating system of VSPP must disconnect itself from the grid system within 0.1 seconds if the frequency at PCC is not in the range of 47Hz-52Hz.   | See table 8     | P       |
| 9  | Anti-Islanding   |                 | P       |
|  | In order to prevent anti-islanding while there is no electricity in grid system to be supplied to the power system of VSPP, the power generating system of VSPP must disconnect itself from the utility system within 1 seconds  | See table 9     | P       |
| 10   | Response to Utility Recovery   |                 | P       |
|  | After the power generating system of VSPP disconnect itself from the grid system because of power outage or voltage/frequency is out of the ranges, when the grid system is back to normal, the power system of VSPP must delay the time to reconnect itself to the grid system at a minimum of 20 seconds to 5 minutes. | See table 10    | P       |

| 1  | TABLE: Current Harmonics             |        |                             |        |                              |           |       |                                | P      |
|--|--------------------------------------|--------|-----------------------------|--------|------------------------------|-----------|-------|--------------------------------|--------|
| Condition of test                                |                                      |        |                             |        |                              | Power(kW) |       |                                |        |
| supplying power to balance linear loads 33% ±5%  |                                      |        |                             |        |                              | 39.75     |       | P                              |        |
| supplying power to balance linear loads 66 %±5%  |                                      |        |                             |        |                              | 79.60     |       | P                              |        |
| supplying power to balance linear loads 100 %±5% |                                      |        |                             |        |                              | 119.95    |       | P                              |        |
| Order  | Output Current Harmonics Measurement |        |                             |        |                              |           | Phase | Limit<br>(% of output current) | Result |
|  | 33% of rated output current          |        | 66% of rated output current |        | 100% of rated output current |           |       |                                |        |
|  | (A)                                  | (%)    | (A)                         | (%)    | (A)                          | (%)       |       |                                |        |
| 1  | 57.450                               | 99.623 | 114.807                     | 99.544 | 172.270                      | 99.578    | L1    | -                              | P      |
| 2  | 0.462                                | 0.804  | 0.781                       | 0.677  | 1.685                        | 0.974     | L1    | <1%                            | P      |
| 3  | 0.165                                | 0.288  | 0.417                       | 0.362  | 0.791                        | 0.457     | L1    | <4%                            | P      |
| 4  | 0.113                                | 0.197  | 0.232                       | 0.201  | 0.571                        | 0.330     | L1    | <1%                            | P      |
| 5  | 0.883                                | 1.537  | 2.127                       | 1.844  | 4.214                        | 2.436     | L1    | <4%                            | P      |
| 6  | 0.032                                | 0.055  | 0.085                       | 0.074  | 0.251                        | 0.145     | L1    | <1%                            | P      |
| 7  | 0.755                                | 1.314  | 1.586                       | 1.375  | 2.906                        | 1.680     | L1    | <4%                            | P      |
| 8  | 0.029                                | 0.051  | 0.048                       | 0.042  | 0.100                        | 0.058     | L1    | <1%                            | P      |
| 9  | 0.076                                | 0.133  | 0.134                       | 0.116  | 0.159                        | 0.092     | L1    | <4%                            | P      |
| 10   | 0.035                                | 0.061  | 0.077                       | 0.067  | 0.266                        | 0.154     | L1    | <1%                            | P      |
| 11   | 0.407                                | 0.708  | 1.036                       | 0.898  | 2.126                        | 1.229     | L1    | <2%                            | P      |
| 12   | 0.014                                | 0.025  | 0.044                       | 0.038  | 0.109                        | 0.063     | L1    | <0.5%                          | P      |
| 13   | 0.307                                | 0.534  | 0.702                       | 0.609  | 1.048                        | 0.606     | L1    | <2%                            | P      |
| 14   | 0.011                                | 0.019  | 0.039                       | 0.034  | 0.133                        | 0.077     | L1    | <0.5%                          | P      |
| 15   | 0.094                                | 0.163  | 0.211                       | 0.183  | 0.199                        | 0.115     | L1    | <2%                            | P      |
| 16   | 0.070                                | 0.122  | 0.209                       | 0.181  | 0.429                        | 0.248     | L1    | <0.5%                          | P      |
| 17   | 0.250                                | 0.435  | 0.691                       | 0.599  | 0.590                        | 0.341     | L1    | <1.5%                          | P      |
| 18   | 0.018                                | 0.031  | 0.054                       | 0.047  | 0.067                        | 0.039     | L1    | <0.375%                        | P      |
| 19   | 0.325                                | 0.565  | 0.373                       | 0.323  | 0.410                        | 0.237     | L1    | <1.5%                          | P      |
| 20   | 0.035                                | 0.061  | 0.082                       | 0.071  | 0.213                        | 0.123     | L1    | <0.375%                        | P      |
| 21   | 0.037                                | 0.064  | 0.123                       | 0.107  | 0.221                        | 0.128     | L1    | <1.5%                          | P      |
| 22   | 0.017                                | 0.029  | 0.024                       | 0.021  | 0.066                        | 0.038     | L1    | <0.375%                        | P      |
| 23   | 0.030                                | 0.052  | 0.188                       | 0.163  | 0.896                        | 0.518     | L1    | <0.6%                          | P      |
| 24   | 0.003                                | 0.005  | 0.044                       | 0.038  | 0.087                        | 0.050     | L1    | <0.15%                         | P      |
| 25   | 0.049                                | 0.086  | 0.149                       | 0.129  | 0.521                        | 0.301     | L1    | <0.6%                          | P      |
| 26   | 0.013                                | 0.023  | 0.068                       | 0.059  | 0.154                        | 0.089     | L1    | <0.15%                         | P      |
| 27   | 0.005                                | 0.008  | 0.013                       | 0.011  | 0.028                        | 0.016     | L1    | <0.6%                          | P      |
| 28   | 0.002                                | 0.003  | 0.016                       | 0.014  | 0.043                        | 0.025     | L1    | <0.15%                         | P      |
| 29   | 0.007                                | 0.012  | 0.043                       | 0.037  | 0.206                        | 0.119     | L1    | <0.6%                          | P      |
| 30   | 0.002                                | 0.003  | 0.010                       | 0.009  | 0.026                        | 0.015     | L1    | <0.15%                         | P      |
| 31   | 0.016                                | 0.027  | 0.067                       | 0.058  | 0.211                        | 0.122     | L1    | <0.6%                          | P      |
| 32   | 0.006                                | 0.010  | 0.020                       | 0.017  | 0.045                        | 0.026     | L1    | <0.15%                         | P      |
| 33   | 0.001                                | 0.002  | 0.007                       | 0.006  | 0.052                        | 0.030     | L1    | <0.6%                          | P      |
| 34   | 0.001                                | 0.002  | 0.008                       | 0.007  | 0.028                        | 0.016     | L1    | <0.15%                         | P      |
| 35   | 0.003                                | 0.006  | 0.030                       | 0.026  | 0.145                        | 0.084     | L1    | <0.3%                          | P      |
| 36   | 0.000                                | 0.000  | 0.006                       | 0.005  | 0.014                        | 0.008     | L1    | <0.075%                        | P      |
| 37   | 0.006                                | 0.011  | 0.062                       | 0.054  | 0.142                        | 0.082     | L1    | <0.3%                          | P      |
| 38   | 0.002                                | 0.003  | 0.015                       | 0.013  | 0.055                        | 0.032     | L1    | <0.075%                        | P      |
| 39   | 0.001                                | 0.002  | 0.013                       | 0.011  | 0.042                        | 0.024     | L1    | <0.3%                          | P      |
| 40   | 0.003                                | 0.006  | 0.016                       | 0.014  | 0.062                        | 0.036     | L1    | <0.075%                        | P      |
| THDi   | --                                   | 2.713  | ---                         | 2.325  | ---                          | 2.211     | L1    | ≤ 5%                           | P      |
| Supplementary information:                       |                                      |        |                             |        |                              |           |       |                                |        |

| 1  | TABLE: Current Harmonics             |        |                             |        |                              |            |       |                                | P      |
|--|--------------------------------------|--------|-----------------------------|--------|------------------------------|------------|-------|--------------------------------|--------|
| Condition of test                                |                                      |        |                             |        |                              | Power (kW) |       |                                |        |
| supplying power to balance linear loads 33% ±5%  |                                      |        |                             |        |                              | 39.75      |       | P                              |        |
| supplying power to balance linear loads 66 %±5%  |                                      |        |                             |        |                              | 79.60      |       | P                              |        |
| supplying power to balance linear loads 100 %±5% |                                      |        |                             |        |                              | 119.95     |       | P                              |        |
| Order  | Output Current Harmonics Measurement |        |                             |        |                              |            | Phase | Limit<br>(% of output current) | Result |
|  | 33% of rated output current          |        | 66% of rated output current |        | 100% of rated output current |            |       |                                |        |
|  | (A)                                  | (%)    | (A)                         | (%)    | (A)                          | (%)        |       |                                |        |
| 1  | 57.393                               | 99.427 | 114.782                     | 99.471 | 172.102                      | 99.426     | L2    | P                              |        |
| 2  | 0.564                                | 0.982  | 1.025                       | 0.889  | 1.709                        | 0.988      | L2    | <1%                            | P      |
| 3  | 0.247                                | 0.430  | 0.482                       | 0.418  | 1.125                        | 0.650      | L2    | <4%                            | P      |
| 4  | 0.072                                | 0.125  | 0.194                       | 0.168  | 0.370                        | 0.214      | L2    | <1%                            | P      |
| 5  | 1.202                                | 2.092  | 1.992                       | 1.727  | 4.818                        | 2.785      | L2    | <4%                            | P      |
| 6  | 0.025                                | 0.043  | 0.103                       | 0.089  | 0.182                        | 0.105      | L2    | <1%                            | P      |
| 7  | 0.719                                | 1.251  | 1.372                       | 1.190  | 2.725                        | 1.575      | L2    | <4%                            | P      |
| 8  | 0.024                                | 0.042  | 0.059                       | 0.051  | 0.100                        | 0.058      | L2    | <1%                            | P      |
| 9  | 0.064                                | 0.111  | 0.142                       | 0.123  | 0.273                        | 0.158      | L2    | <4%                            | P      |
| 10   | 0.051                                | 0.088  | 0.076                       | 0.066  | 0.261                        | 0.151      | L2    | <1%                            | P      |
| 11   | 0.439                                | 0.764  | 0.592                       | 0.513  | 2.005                        | 1.159      | L2    | <2%                            | P      |
| 12   | 0.020                                | 0.035  | 0.032                       | 0.028  | 0.085                        | 0.049      | L2    | <0.5%                          | P      |
| 13   | 0.349                                | 0.607  | 0.563                       | 0.488  | 1.182                        | 0.683      | L2    | <2%                            | P      |
| 14   | 0.052                                | 0.090  | 0.088                       | 0.076  | 0.221                        | 0.128      | L2    | <0.5%                          | P      |
| 15   | 0.145                                | 0.253  | 0.319                       | 0.277  | 0.246                        | 0.142      | L2    | <2%                            | P      |
| 16   | 0.111                                | 0.194  | 0.153                       | 0.133  | 0.573                        | 0.331      | L2    | <0.5%                          | P      |
| 17   | 0.417                                | 0.726  | 0.819                       | 0.710  | 0.794                        | 0.459      | L2    | <1.5%                          | P      |
| 18   | 0.027                                | 0.047  | 0.051                       | 0.044  | 0.092                        | 0.053      | L2    | <0.375%                        | P      |
| 19   | 0.204                                | 0.355  | 0.490                       | 0.425  | 0.734                        | 0.424      | L2    | <1.5%                          | P      |
| 20   | 0.044                                | 0.076  | 0.072                       | 0.062  | 0.270                        | 0.156      | L2    | <0.375%                        | P      |
| 21   | 0.047                                | 0.082  | 0.103                       | 0.089  | 0.242                        | 0.140      | L2    | <1.5%                          | P      |
| 22   | 0.036                                | 0.062  | 0.042                       | 0.036  | 0.073                        | 0.042      | L2    | <0.375%                        | P      |
| 23   | 0.114                                | 0.198  | 0.158                       | 0.137  | 0.756                        | 0.437      | L2    | <0.6%                          | P      |
| 24   | 0.005                                | 0.009  | 0.020                       | 0.017  | 0.071                        | 0.041      | L2    | <0.15%                         | P      |
| 25   | 0.064                                | 0.112  | 0.057                       | 0.049  | 0.465                        | 0.269      | L2    | <0.6%                          | P      |
| 26   | 0.014                                | 0.024  | 0.008                       | 0.007  | 0.088                        | 0.051      | L2    | <0.15%                         | P      |
| 27   | 0.008                                | 0.014  | 0.016                       | 0.014  | 0.038                        | 0.022      | L2    | <0.6%                          | P      |
| 28   | 0.004                                | 0.007  | 0.002                       | 0.002  | 0.040                        | 0.023      | L2    | <0.15%                         | P      |
| 29   | 0.025                                | 0.043  | 0.024                       | 0.021  | 0.216                        | 0.125      | L2    | <0.6%                          | P      |
| 30   | 0.004                                | 0.007  | 0.001                       | 0.001  | 0.029                        | 0.017      | L2    | <0.15%                         | P      |
| 31   | 0.039                                | 0.068  | 0.031                       | 0.027  | 0.223                        | 0.129      | L2    | <0.6%                          | P      |
| 32   | 0.009                                | 0.016  | 0.012                       | 0.010  | 0.055                        | 0.032      | L2    | <0.15%                         | P      |
| 33   | 0.002                                | 0.004  | 0.000                       | 0.000  | 0.029                        | 0.017      | L2    | <0.6%                          | P      |
| 34   | 0.003                                | 0.005  | 0.002                       | 0.002  | 0.033                        | 0.019      | L2    | <0.15%                         | P      |
| 35   | 0.009                                | 0.015  | 0.001                       | 0.001  | 0.097                        | 0.056      | L2    | <0.3%                          | P      |
| 36   | 0.003                                | 0.006  | 0.003                       | 0.003  | 0.017                        | 0.010      | L2    | <0.075%                        | P      |
| 37   | 0.028                                | 0.049  | 0.008                       | 0.007  | 0.168                        | 0.097      | L2    | <0.3%                          | P      |
| 38   | 0.007                                | 0.013  | 0.000                       | 0.001  | 0.059                        | 0.034      | L2    | <0.075%                        | P      |
| 39   | 0.007                                | 0.012  | 0.009                       | 0.008  | 0.021                        | 0.012      | L2    | <0.3%                          | P      |
| 40   | 0.011                                | 0.019  | 0.001                       | 0.001  | 0.087                        | 0.050      | L2    | <0.075%                        | P      |
| THDi   | ---                                  | 2.472  | ---                         | 2.449  | ---                          | 2.125      | L2    | ≤ 5%                           | P      |
| Supplementary information:                       |                                      |        |                             |        |                              |            |       |                                |        |

|                            |  |        |                                |        |                                 |        |           |                                   |        |
|----------------------------|--|--------|--------------------------------|--------|---------------------------------|--------|-----------|-----------------------------------|--------|
| 1                          | TABLE: Current Harmonics                         |        |                                |        |                                 |        |           |                                   | P      |
|                            | Condition of test                                |        |                                |        |                                 |        | Power(kW) |                                   |        |
|                            | supplying power to balance linear loads 33% ±5%  |        |                                |        |                                 |        | 39.75     |                                   | P      |
|                            | supplying power to balance linear loads 66 %±5%  |        |                                |        |                                 |        | 79.60     |                                   | P      |
|                            | supplying power to balance linear loads 100 %±5% |        |                                |        |                                 |        | 119.95    |                                   | P      |
|                            | Output Current Harmonics Measurement             |        |                                |        |                                 |        |           | Limit<br>(% of output<br>current) | Result |
| Order                      | 33% of rated<br>output current                   |        | 66% of rated<br>output current |        | 100% of rated<br>output current |        | Phase     |                                   |        |
|                            | (A)  | (%)    | (A)                            | (%)    | (A)                             | (%)    |           |                                   |        |
| 1                          | 57.653   | 99.926 | 115.286                        | 99.952 | 172.902                         | 99.975 | L3        | P                                 |        |
| 2                          | 0.200  | 0.677  | 1.123                          | 0.974  | 1.391                           | 0.804  | L3        | <1%                               | P      |
| 3                          | 0.108  | 0.362  | 0.527                          | 0.457  | 0.498                           | 0.288  | L3        | <4%                               | P      |
| 4                          | 0.060  | 0.201  | 0.381                          | 0.330  | 0.341                           | 0.197  | L3        | <1%                               | P      |
| 5                          | 0.544  | 1.844  | 2.809                          | 2.436  | 2.659                           | 1.537  | L3        | <4%                               | P      |
| 6                          | 0.023  | 0.074  | 0.167                          | 0.145  | 0.095                           | 0.055  | L3        | <1%                               | P      |
| 7                          | 0.406  | 1.375  | 1.938                          | 1.680  | 2.273                           | 1.314  | L3        | <4%                               | P      |
| 8                          | 0.013  | 0.042  | 0.067                          | 0.058  | 0.088                           | 0.051  | L3        | <1%                               | P      |
| 9                          | 0.035  | 0.116  | 0.106                          | 0.092  | 0.230                           | 0.133  | L3        | <4%                               | P      |
| 10                         | 0.021  | 0.067  | 0.178                          | 0.154  | 0.106                           | 0.061  | L3        | <1%                               | P      |
| 11                         | 0.265  | 0.898  | 1.417                          | 1.229  | 1.225                           | 0.708  | L3        | <2%                               | P      |
| 12                         | 0.012  | 0.038  | 0.073                          | 0.063  | 0.043                           | 0.025  | L3        | <0.5%                             | P      |
| 13                         | 0.180  | 0.609  | 0.699                          | 0.606  | 0.924                           | 0.534  | L3        | <2%                               | P      |
| 14                         | 0.011  | 0.034  | 0.089                          | 0.077  | 0.033                           | 0.019  | L3        | <0.5%                             | P      |
| 15                         | 0.055  | 0.183  | 0.133                          | 0.115  | 0.282                           | 0.163  | L3        | <2%                               | P      |
| 16                         | 0.054  | 0.181  | 0.286                          | 0.248  | 0.211                           | 0.122  | L3        | <0.5%                             | P      |
| 17                         | 0.177  | 0.599  | 0.393                          | 0.341  | 0.753                           | 0.435  | L3        | <1.5%                             | P      |
| 18                         | 0.015  | 0.047  | 0.045                          | 0.039  | 0.054                           | 0.031  | L3        | <0.375%                           | P      |
| 19                         | 0.096  | 0.323  | 0.273                          | 0.237  | 0.977                           | 0.565  | L3        | <1.5%                             | P      |
| 20                         | 0.022  | 0.071  | 0.142                          | 0.123  | 0.106                           | 0.061  | L3        | <0.375%                           | P      |
| 21                         | 0.032  | 0.107  | 0.148                          | 0.128  | 0.111                           | 0.064  | L3        | <1.5%                             | P      |
| 22                         | 0.007  | 0.021  | 0.044                          | 0.038  | 0.050                           | 0.029  | L3        | <0.375%                           | P      |
| 23                         | 0.049  | 0.163  | 0.597                          | 0.518  | 0.090                           | 0.052  | L3        | <0.6%                             | P      |
| 24                         | 0.012  | 0.038  | 0.058                          | 0.050  | 0.009                           | 0.005  | L3        | <0.15%                            | P      |
| 25                         | 0.039  | 0.129  | 0.347                          | 0.301  | 0.149                           | 0.086  | L3        | <0.6%                             | P      |
| 26                         | 0.018  | 0.059  | 0.103                          | 0.089  | 0.040                           | 0.023  | L3        | <0.15%                            | P      |
| 27                         | 0.004  | 0.011  | 0.018                          | 0.016  | 0.014                           | 0.008  | L3        | <0.6%                             | P      |
| 28                         | 0.005  | 0.014  | 0.029                          | 0.025  | 0.005                           | 0.003  | L3        | <0.15%                            | P      |
| 29                         | 0.012  | 0.037  | 0.137                          | 0.119  | 0.021                           | 0.012  | L3        | <0.6%                             | P      |
| 30                         | 0.004  | 0.009  | 0.017                          | 0.015  | 0.005                           | 0.003  | L3        | <0.15%                            | P      |
| 31                         | 0.018  | 0.058  | 0.141                          | 0.122  | 0.047                           | 0.027  | L3        | <0.6%                             | P      |
| 32                         | 0.006  | 0.017  | 0.030                          | 0.026  | 0.017                           | 0.010  | L3        | <0.15%                            | P      |
| 33                         | 0.003  | 0.006  | 0.035                          | 0.030  | 0.003                           | 0.002  | L3        | <0.6%                             | P      |
| 34                         | 0.003  | 0.007  | 0.018                          | 0.016  | 0.003                           | 0.002  | L3        | <0.15%                            | P      |
| 35                         | 0.009  | 0.026  | 0.097                          | 0.084  | 0.010                           | 0.006  | L3        | <0.3%                             | P      |
| 36                         | 0.002  | 0.005  | 0.009                          | 0.008  | 0.000                           | 0.000  | L3        | <0.075%                           | P      |
| 37                         | 0.017  | 0.054  | 0.095                          | 0.082  | 0.019                           | 0.011  | L3        | <0.3%                             | P      |
| 38                         | 0.005  | 0.013  | 0.037                          | 0.032  | 0.005                           | 0.003  | L3        | <0.075%                           | P      |
| 39                         | 0.004  | 0.011  | 0.028                          | 0.024  | 0.003                           | 0.002  | L3        | <0.3%                             | P      |
| 40                         | 0.005  | 0.014  | 0.042                          | 0.036  | 0.010                           | 0.006  | L3        | <0.075%                           | P      |
| THDi                       |  | 2.417  |                                | 1.976  |                                 | 2.289  | L3        | ≤ 5%                              | P      |
| Supplementary information: |  |        |                                |        |                                 |        |           |                                   |        |

| 1                                    | TABLE: Voltage Harmonics                         |       |                             |       |                              |       |       | P                           |        |
|--------------------------------------|--|-------|-----------------------------|-------|------------------------------|-------|-------|-----------------------------|--------|
|                                      | Condition of test                                |       |                             |       | Power(kW)                    |       |       |                             |        |
|                                      | supplying power to balance linear loads 33% ±5%  |       |                             |       | 39.75                        |       |       | P                           |        |
|                                      | supplying power to balance linear loads 66 %±5%  |       |                             |       | 79.60                        |       |       | P                           |        |
|                                      | supplying power to balance linear loads 100 %±5% |       |                             |       | 119.95                       |       |       | P                           |        |
| Output Voltage Harmonics Measurement |  |       |                             |       |                              |       |       |                             |        |
| Order                                | 33% of rated output current                      |       | 66% of rated output current |       | 100% of rated output current |       | Phase | Limit (% of output current) | Result |
|                                      | (V)  | (%)   | (V)                         | (%)   | (V)                          | (%)   |       |                             |        |
| 1                                    | 230.01   | 100   | 230.03                      | 100   | 230.18                       | 100   | L1    | -                           | P      |
| 2                                    | 0.177  | 0.077 | 0.186                       | 0.081 | 0.177                        | 0.077 | L1    | <2%                         | P      |
| 3                                    | 1.854  | 0.806 | 1.778                       | 0.773 | 1.854                        | 0.806 | L1    | <4%                         | P      |
| 4                                    | 0.591  | 0.257 | 0.035                       | 0.015 | 0.591                        | 0.257 | L1    | <2%                         | P      |
| 5                                    | 0.276  | 0.120 | 0.313                       | 0.136 | 0.276                        | 0.120 | L1    | <4%                         | P      |
| 6                                    | 0.018  | 0.008 | 0.009                       | 0.004 | 0.018                        | 0.008 | L1    | <2%                         | P      |
| 7                                    | 0.216  | 0.094 | 0.182                       | 0.079 | 0.216                        | 0.094 | L1    | <4%                         | P      |
| 8                                    | 0.002  | 0.001 | 0.005                       | 0.002 | 0.002                        | 0.001 | L1    | <2%                         | P      |
| 9                                    | 0.145  | 0.063 | 0.143                       | 0.062 | 0.145                        | 0.063 | L1    | <4%                         | P      |
| 10                                   | 0.021  | 0.009 | 0.016                       | 0.007 | 0.021                        | 0.009 | L1    | <2%                         | P      |
| 11                                   | 0.104  | 0.045 | 0.062                       | 0.027 | 0.104                        | 0.045 | L1    | <4%                         | P      |
| 12                                   | 0.028  | 0.012 | 0.021                       | 0.009 | 0.028                        | 0.012 | L1    | <2%                         | P      |
| 13                                   | 0.421  | 0.183 | 0.028                       | 0.012 | 0.421                        | 0.183 | L1    | <4%                         | P      |
| 14                                   | 0.152  | 0.066 | 0.018                       | 0.008 | 0.152                        | 0.066 | L1    | <2%                         | P      |
| 15                                   | 0.101  | 0.044 | 0.087                       | 0.038 | 0.101                        | 0.044 | L1    | <4%                         | P      |
| 16                                   | 0.051  | 0.022 | 0.016                       | 0.007 | 0.051                        | 0.022 | L1    | <2%                         | P      |
| 17                                   | 0.472  | 0.205 | 0.092                       | 0.040 | 0.472                        | 0.205 | L1    | <4%                         | P      |
| 18                                   | 0.051  | 0.022 | 0.012                       | 0.005 | 0.051                        | 0.022 | L1    | <2%                         | P      |
| 19                                   | 0.370  | 0.161 | 0.074                       | 0.032 | 0.370                        | 0.161 | L1    | <4%                         | P      |
| 20                                   | 0.012  | 0.005 | 0.012                       | 0.005 | 0.012                        | 0.005 | L1    | <2%                         | P      |
| 21                                   | 0.104  | 0.045 | 0.104                       | 0.045 | 0.104                        | 0.045 | L1    | <4%                         | P      |
| 22                                   | 0.009  | 0.004 | 0.009                       | 0.004 | 0.009                        | 0.004 | L1    | <2%                         | P      |
| 23                                   | 0.051  | 0.022 | 0.051                       | 0.022 | 0.051                        | 0.022 | L1    | <4%                         | P      |
| 24                                   | 0.009  | 0.004 | 0.009                       | 0.004 | 0.009                        | 0.004 | L1    | <2%                         | P      |
| 25                                   | 0.046  | 0.020 | 0.046                       | 0.020 | 0.046                        | 0.020 | L1    | <4%                         | P      |
| 26                                   | 0.014  | 0.006 | 0.014                       | 0.006 | 0.014                        | 0.006 | L1    | <2%                         | P      |
| 27                                   | 0.051  | 0.022 | 0.044                       | 0.019 | 0.051                        | 0.022 | L1    | <4%                         | P      |
| 28                                   | 0.085  | 0.037 | 0.014                       | 0.006 | 0.085                        | 0.037 | L1    | <2%                         | P      |
| 29                                   | 0.101  | 0.044 | 0.037                       | 0.016 | 0.101                        | 0.044 | L1    | <4%                         | P      |
| 30                                   | 0.016  | 0.007 | 0.016                       | 0.007 | 0.016                        | 0.007 | L1    | <2%                         | P      |
| 31                                   | 0.117  | 0.051 | 0.023                       | 0.010 | 0.117                        | 0.051 | L1    | <4%                         | P      |
| 32                                   | 0.051  | 0.022 | 0.007                       | 0.003 | 0.051                        | 0.022 | L1    | <2%                         | P      |
| 33                                   | 0.035  | 0.015 | 0.009                       | 0.004 | 0.035                        | 0.015 | L1    | <4%                         | P      |
| 34                                   | 0.131  | 0.057 | 0.005                       | 0.002 | 0.131                        | 0.057 | L1    | <2%                         | P      |
| 35                                   | 0.064  | 0.028 | 0.007                       | 0.003 | 0.064                        | 0.028 | L1    | <4%                         | P      |
| 36                                   | 0.037  | 0.016 | 0.009                       | 0.004 | 0.037                        | 0.016 | L1    | <2%                         | P      |
| 37                                   | 0.097  | 0.042 | 0.039                       | 0.017 | 0.097                        | 0.042 | L1    | <4%                         | P      |
| 38                                   | 0.014  | 0.006 | 0.012                       | 0.005 | 0.014                        | 0.006 | L1    | <2%                         | P      |
| 39                                   | 0.014  | 0.006 | 0.037                       | 0.016 | 0.014                        | 0.006 | L1    | <4%                         | P      |
| 40                                   | 0.014  | 0.006 | 0.005                       | 0.002 | 0.014                        | 0.006 | L1    | <2%                         | P      |
| THDv                                 | --   | 0.843 | --                          | 0.816 | --                           | 0.892 | L1    | ≤ 5%                        | P      |
| Supplementary information:           |  |       |                             |       |                              |       |       |                             |        |

| 1                                    | TABLE: Voltage Harmonics                         |       |                             |       |                              |       |       | P                           |        |
|--------------------------------------|--|-------|-----------------------------|-------|------------------------------|-------|-------|-----------------------------|--------|
|                                      | Condition of test                                |       |                             |       | Power(kW)                    |       |       |                             |        |
|                                      | supplying power to balance linear loads 33% ±5%  |       |                             |       | 39.75                        |       |       | P                           |        |
|                                      | supplying power to balance linear loads 66 %±5%  |       |                             |       | 79.60                        |       |       | P                           |        |
|                                      | supplying power to balance linear loads 100 %±5% |       |                             |       | 119.95                       |       |       | P                           |        |
| Output Voltage Harmonics Measurement |  |       |                             |       |                              |       |       |                             |        |
| Order                                | 33% of rated output current                      |       | 66% of rated output current |       | 100% of rated output current |       | Phase | Limit (% of output current) | Result |
|                                      | (V)  | (%)   | (V)                         | (%)   | (V)                          | (%)   |       |                             |        |
| 1                                    | 230.03   | 100   | 230.31                      | 100   | 230.01                       | 100   | L2    | -                           | P      |
| 2                                    | 0.169  | 0.077 | 0.189                       | 0.082 | 0.177                        | 0.077 | L2    | <2%                         | P      |
| 3                                    | 1.773  | 0.806 | 1.803                       | 0.784 | 1.854                        | 0.806 | L2    | <4%                         | P      |
| 4                                    | 0.565  | 0.257 | 0.018                       | 0.008 | 0.591                        | 0.257 | L2    | <2%                         | P      |
| 5                                    | 0.264  | 0.120 | 0.216                       | 0.094 | 0.276                        | 0.120 | L2    | <4%                         | P      |
| 6                                    | 0.018  | 0.008 | 0.002                       | 0.001 | 0.018                        | 0.008 | L2    | <2%                         | P      |
| 7                                    | 0.207  | 0.094 | 0.145                       | 0.063 | 0.216                        | 0.094 | L2    | <4%                         | P      |
| 8                                    | 0.002  | 0.001 | 0.021                       | 0.009 | 0.002                        | 0.001 | L2    | <2%                         | P      |
| 9                                    | 0.139  | 0.063 | 0.104                       | 0.045 | 0.145                        | 0.063 | L2    | <4%                         | P      |
| 10                                   | 0.020  | 0.009 | 0.028                       | 0.012 | 0.021                        | 0.009 | L2    | <2%                         | P      |
| 11                                   | 0.099  | 0.045 | 0.421                       | 0.183 | 0.104                        | 0.045 | L2    | <4%                         | P      |
| 12                                   | 0.026  | 0.012 | 0.028                       | 0.012 | 0.028                        | 0.012 | L2    | <2%                         | P      |
| 13                                   | 0.403  | 0.183 | 0.046                       | 0.020 | 0.421                        | 0.183 | L2    | <4%                         | P      |
| 14                                   | 0.145  | 0.066 | 0.023                       | 0.010 | 0.152                        | 0.066 | L2    | <2%                         | P      |
| 15                                   | 0.087  | 0.038 | 0.087                       | 0.038 | 0.101                        | 0.044 | L2    | <4%                         | P      |
| 16                                   | 0.016  | 0.007 | 0.021                       | 0.009 | 0.051                        | 0.022 | L2    | <2%                         | P      |
| 17                                   | 0.092  | 0.040 | 0.099                       | 0.043 | 0.472                        | 0.205 | L2    | <4%                         | P      |
| 18                                   | 0.012  | 0.005 | 0.014                       | 0.006 | 0.051                        | 0.022 | L2    | <2%                         | P      |
| 19                                   | 0.074  | 0.032 | 0.064                       | 0.028 | 0.370                        | 0.161 | L2    | <4%                         | P      |
| 20                                   | 0.012  | 0.005 | 0.009                       | 0.004 | 0.012                        | 0.005 | L2    | <2%                         | P      |
| 21                                   | 0.092  | 0.040 | 0.097                       | 0.042 | 0.104                        | 0.045 | L2    | <4%                         | P      |
| 22                                   | 0.007  | 0.003 | 0.005                       | 0.002 | 0.009                        | 0.004 | L2    | <2%                         | P      |
| 23                                   | 0.067  | 0.029 | 0.051                       | 0.022 | 0.051                        | 0.022 | L2    | <4%                         | P      |
| 24                                   | 0.012  | 0.005 | 0.009                       | 0.004 | 0.009                        | 0.004 | L2    | <2%                         | P      |
| 25                                   | 0.035  | 0.015 | 0.032                       | 0.014 | 0.046                        | 0.020 | L2    | <4%                         | P      |
| 26                                   | 0.016  | 0.007 | 0.012                       | 0.005 | 0.014                        | 0.006 | L2    | <2%                         | P      |
| 27                                   | 0.051  | 0.022 | 0.044                       | 0.019 | 0.051                        | 0.022 | L2    | <4%                         | P      |
| 28                                   | 0.021  | 0.009 | 0.016                       | 0.007 | 0.085                        | 0.037 | L2    | <2%                         | P      |
| 29                                   | 0.030  | 0.013 | 0.030                       | 0.013 | 0.101                        | 0.044 | L2    | <4%                         | P      |
| 30                                   | 0.016  | 0.007 | 0.014                       | 0.006 | 0.016                        | 0.007 | L2    | <2%                         | P      |
| 31                                   | 0.014  | 0.006 | 0.023                       | 0.010 | 0.117                        | 0.051 | L2    | <4%                         | P      |
| 32                                   | 0.009  | 0.004 | 0.009                       | 0.004 | 0.051                        | 0.022 | L2    | <2%                         | P      |
| 33                                   | 0.007  | 0.003 | 0.005                       | 0.002 | 0.035                        | 0.015 | L2    | <4%                         | P      |
| 34                                   | 0.009  | 0.004 | 0.007                       | 0.003 | 0.131                        | 0.057 | L2    | <2%                         | P      |
| 35                                   | 0.005  | 0.002 | 0.005                       | 0.002 | 0.064                        | 0.028 | L2    | <4%                         | P      |
| 36                                   | 0.009  | 0.004 | 0.007                       | 0.003 | 0.037                        | 0.016 | L2    | <2%                         | P      |
| 37                                   | 0.041  | 0.018 | 0.041                       | 0.018 | 0.097                        | 0.042 | L2    | <4%                         | P      |
| 38                                   | 0.009  | 0.004 | 0.009                       | 0.004 | 0.014                        | 0.006 | L2    | <2%                         | P      |
| 39                                   | 0.037  | 0.016 | 0.035                       | 0.015 | 0.014                        | 0.006 | L2    | <4%                         | P      |
| 40                                   | 0.007  | 0.003 | 0.007                       | 0.003 | 0.014                        | 0.006 | L2    | <2%                         | P      |
| THDv                                 | --   | 0.838 | --                          | 0.826 | --                           | 0.901 | L2    | ≤ 5%                        | P      |
| Supplementary information:           |  |       |                             |       |                              |       |       |                             |        |

| 1                                    | TABLE: Voltage Harmonics                         |       |                             |       |                              |       |       | P                           |        |
|--------------------------------------|--|-------|-----------------------------|-------|------------------------------|-------|-------|-----------------------------|--------|
|                                      | Condition of test                                |       |                             |       | Power(kW)                    |       |       |                             |        |
|                                      | supplying power to balance linear loads 33% ±5%  |       |                             |       | 39.75                        |       |       | P                           |        |
|                                      | supplying power to balance linear loads 66 %±5%  |       |                             |       | 79.60                        |       |       | P                           |        |
|                                      | supplying power to balance linear loads 100 %±5% |       |                             |       | 119.95                       |       |       | P                           |        |
| Output Voltage Harmonics Measurement |  |       |                             |       |                              |       |       |                             |        |
| Order                                | 33% of rated output current                      |       | 66% of rated output current |       | 100% of rated output current |       | Phase | Limit (% of output current) | Result |
|                                      | (V)  | (%)   | (V)                         | (%)   | (V)                          | (%)   |       |                             |        |
| 1                                    | 230.08   | 100   | 230.13                      | 100   | 230.01                       | 100   | L3    | -                           | P      |
| 2                                    | 0.179  | 0.078 | 0.172                       | 0.077 | 0.169                        | 0.077 | L3    | <2%                         | P      |
| 3                                    | 1.792  | 0.779 | 1.714                       | 0.806 | 1.773                        | 0.806 | L3    | <4%                         | P      |
| 4                                    | 0.037  | 0.016 | 0.035                       | 0.257 | 0.565                        | 0.257 | L3    | <2%                         | P      |
| 5                                    | 0.281  | 0.122 | 0.268                       | 0.120 | 0.264                        | 0.120 | L3    | <4%                         | P      |
| 6                                    | 0.016  | 0.007 | 0.015                       | 0.008 | 0.018                        | 0.008 | L3    | <2%                         | P      |
| 7                                    | 0.225  | 0.098 | 0.216                       | 0.094 | 0.207                        | 0.094 | L3    | <4%                         | P      |
| 8                                    | 0.002  | 0.001 | 0.002                       | 0.001 | 0.002                        | 0.001 | L3    | <2%                         | P      |
| 9                                    | 0.161  | 0.070 | 0.154                       | 0.063 | 0.139                        | 0.063 | L3    | <4%                         | P      |
| 10                                   | 0.016  | 0.007 | 0.015                       | 0.009 | 0.020                        | 0.009 | L3    | <2%                         | P      |
| 11                                   | 0.062  | 0.027 | 0.095                       | 0.045 | 0.099                        | 0.045 | L3    | <4%                         | P      |
| 12                                   | 0.021  | 0.009 | 0.022                       | 0.012 | 0.026                        | 0.012 | L3    | <2%                         | P      |
| 13                                   | 0.028  | 0.012 | 0.044                       | 0.183 | 0.403                        | 0.183 | L3    | <4%                         | P      |
| 14                                   | 0.018  | 0.008 | 0.022                       | 0.066 | 0.145                        | 0.066 | L3    | <2%                         | P      |
| 15                                   | 0.087  | 0.038 | 0.097                       | 0.044 | 0.097                        | 0.044 | L3    | <4%                         | P      |
| 16                                   | 0.016  | 0.009 | 0.020                       | 0.010 | 0.048                        | 0.022 | L3    | <2%                         | P      |
| 17                                   | 0.092  | 0.043 | 0.095                       | 0.045 | 0.451                        | 0.205 | L3    | <4%                         | P      |
| 18                                   | 0.012  | 0.006 | 0.013                       | 0.007 | 0.048                        | 0.022 | L3    | <2%                         | P      |
| 19                                   | 0.074  | 0.028 | 0.062                       | 0.027 | 0.354                        | 0.161 | L3    | <4%                         | P      |
| 20                                   | 0.012  | 0.004 | 0.011                       | 0.005 | 0.011                        | 0.005 | L3    | <2%                         | P      |
| 21                                   | 0.092  | 0.042 | 0.099                       | 0.045 | 0.099                        | 0.045 | L3    | <4%                         | P      |
| 22                                   | 0.007  | 0.002 | 0.009                       | 0.004 | 0.009                        | 0.004 | L3    | <2%                         | P      |
| 23                                   | 0.067  | 0.022 | 0.048                       | 0.022 | 0.048                        | 0.022 | L3    | <4%                         | P      |
| 24                                   | 0.012  | 0.004 | 0.009                       | 0.004 | 0.009                        | 0.004 | L3    | <2%                         | P      |
| 25                                   | 0.035  | 0.014 | 0.044                       | 0.020 | 0.044                        | 0.020 | L3    | <4%                         | P      |
| 26                                   | 0.016  | 0.005 | 0.013                       | 0.006 | 0.013                        | 0.006 | L3    | <2%                         | P      |
| 27                                   | 0.051  | 0.019 | 0.042                       | 0.019 | 0.048                        | 0.022 | L3    | <4%                         | P      |
| 28                                   | 0.021  | 0.007 | 0.013                       | 0.006 | 0.081                        | 0.037 | L3    | <2%                         | P      |
| 29                                   | 0.030  | 0.013 | 0.035                       | 0.016 | 0.097                        | 0.044 | L3    | <4%                         | P      |
| 30                                   | 0.016  | 0.006 | 0.015                       | 0.007 | 0.015                        | 0.007 | L3    | <2%                         | P      |
| 31                                   | 0.014  | 0.010 | 0.022                       | 0.010 | 0.112                        | 0.051 | L3    | <4%                         | P      |
| 32                                   | 0.009  | 0.004 | 0.007                       | 0.003 | 0.048                        | 0.022 | L3    | <2%                         | P      |
| 33                                   | 0.007  | 0.002 | 0.009                       | 0.004 | 0.033                        | 0.015 | L3    | <4%                         | P      |
| 34                                   | 0.009  | 0.003 | 0.004                       | 0.002 | 0.125                        | 0.057 | L3    | <2%                         | P      |
| 35                                   | 0.005  | 0.002 | 0.007                       | 0.003 | 0.062                        | 0.028 | L3    | <4%                         | P      |
| 36                                   | 0.009  | 0.003 | 0.009                       | 0.004 | 0.035                        | 0.016 | L3    | <2%                         | P      |
| 37                                   | 0.041  | 0.018 | 0.037                       | 0.017 | 0.092                        | 0.042 | L3    | <4%                         | P      |
| 38                                   | 0.009  | 0.004 | 0.011                       | 0.005 | 0.013                        | 0.006 | L3    | <2%                         | P      |
| 39                                   | 0.037  | 0.015 | 0.035                       | 0.016 | 0.013                        | 0.006 | L3    | <4%                         | P      |
| 40                                   | 0.007  | 0.003 | 0.004                       | 0.002 | 0.013                        | 0.006 | L3    | <2%                         | P      |
| THDv                                 | --   | 0.829 | --                          | 0.834 | --                           | 0.907 | L3    | ≤ 5%                        | P      |
| Supplementary information:           |  |       |                             |       |                              |       |       |                             |        |

| 2                          | TABLE: Voltage Fluctuation |      |      |       |        | P |
|----------------------------|----------------------------|------|------|-------|--------|---|
| Flicker measurement 1      | EUT values                 |      |      | Limit | Result |   |
|                            | L1                         | L2   | L3   |       |        |   |
| Pst                        | 0.22                       | 0.23 | 0.24 | 1.00  | P      |   |
| Plt                        | 0.26                       | 0.21 | 0.22 | 0.80  | P      |   |
| dc [%]                     | 0.07                       | 0.06 | 0.07 | 3.30  | P      |   |
| dmax [%]                   | 0.78                       | 0.82 | 0.80 | 4.00  | P      |   |
| dt [s]                     | 0                          | 0    | 0    | --    | -      |   |
| Supplementary information: |                            |      |      |       |        |   |

| 3  | TABLE: Direct Current Injection |       |                             |       |                              | P     |           |               |
|--|---------------------------------|-------|-----------------------------|-------|------------------------------|-------|-----------|---------------|
| Condition of test                                |                                 |       |                             |       | Output Power [kW]            |       |           |               |
| supplying power to balance linear loads 33% ±5%  |                                 |       |                             |       | 39.75                        | P     |           |               |
| supplying power to balance linear loads 66% ±5%  |                                 |       |                             |       | 79.60                        | P     |           |               |
| supplying power to balance linear loads 100% ±5% |                                 |       |                             |       | 119.95                       | P     |           |               |
| Normal rated output current                      |                                 |       |                             |       | 173A                         |       |           |               |
| Phase  | Output DC current Measurement   |       |                             |       |                              |       | Limit [%] | Verdict [P/F] |
|  | 33% of rated output current     |       | 66% of rated output current |       | 100% of rated output current |       |           |               |
|  | (A)                             | (%)   | (A)                         | (%)   | (A)                          | (%)   |           |               |
| L1   | 0.147                           | 0.258 | 0.182                       | 0.157 | 0.163                        | 0.094 | ≤0.5      | P             |
| L2   | 0.152                           | 0.258 | 0.146                       | 0.126 | 0.179                        | 0.103 | ≤0.5      | P             |
| L3   | 0.143                           | 0.257 | 0.127                       | 0.110 | 0.155                        | 0.090 | ≤0.5      | P             |
| Supplementary information:                       |                                 |       |                             |       |                              |       |           |               |

| 4             | TABLE : Reactive power control |       |                |        |          |        | P            |
|---------------|--------------------------------|-------|----------------|--------|----------|--------|--------------|
| -Q max        |                                |       |                |        |          |        |              |
| Power Set [%] | Active Power                   |       | Reactive power |        | DC power |        | Power factor |
|               | kW                             | p.u.  | kVAR           | p.u.   | (kW)     | p.u.   |              |
| 1             | 4.140                          | 0.037 | -121.128       | -1.000 | 4.512    | 0.0347 | 0.034272     |
| 10            | 11.088                         | 0.095 | -120.696       | -0.996 | 11.976   | 0.0992 | 0.091424     |
| 20            | 25.500                         | 0.216 | -118.488       | -0.978 | 27.456   | 0.3327 | 0.211442     |
| 30            | 36.396                         | 0.306 | -115.608       | -0.954 | 38.640   | 0.3943 | 0.301035     |
| 40            | 47.100                         | 0.396 | -111.672       | -0.921 | 49.464   | 0.4187 | 0.389421     |
| 50            | 60.288                         | 0.506 | -105.144       | -0.867 | 62.016   | 0.5192 | 0.507417     |
| 60            | 72.936                         | 0.611 | -96.792        | -0.797 | 74.736   | 0.6201 | 0.601782     |
| 70            | 84.432                         | 0.707 | -86.952        | -0.715 | 86.328   | 0.7114 | 0.694325     |
| 80            | 96.300                         | 0.806 | -73.584        | -0.603 | 97.968   | 0.8162 | 0.809923     |
| 90            | 108.276                        | 0.906 | -54.456        | -0.444 | 109.920  | 0.9097 | 0.893396     |
| 100           | 119.856                        | 1.000 | -18.000        | -0.203 | 121.440  | 1.0000 | 0.990924     |


| +Q max    |                  |       |                      |       |          |        |              |
|-----------|------------------|-------|----------------------|-------|----------|--------|--------------|
| Power Set | Active Power [W] |       | Reactive power [Var] |       | DC power |        | Power factor |
|           | kW               | p.u.  | kVAR                 | p.u.  | (kW)     | p.u.   |              |
| 1         | 4.380            | 0.039 | 121.128              | 1.017 | 4.800    | 0.0407 | 0.036153     |
| 10        | 11.364           | 0.098 | 120.672              | 0.998 | 12.072   | 0.1004 | 0.093776     |
| 20        | 26.136           | 0.221 | 118.344              | 0.971 | 27.456   | 0.2269 | 0.215658     |
| 30        | 37.980           | 0.319 | 115.104              | 0.942 | 39.240   | 0.3238 | 0.313380     |
| 40        | 47.232           | 0.397 | 111.624              | 0.887 | 48.288   | 0.3983 | 0.389717     |
| 50        | 60.528           | 0.508 | 105.000              | 0.822 | 61.584   | 0.5075 | 0.499420     |
| 60        | 72.384           | 0.606 | 97.200               | 0.738 | 73.488   | 0.6054 | 0.597242     |
| 70        | 84.252           | 0.705 | 87.120               | 0.618 | 85.968   | 0.7081 | 0.695163     |
| 80        | 96.900           | 0.811 | 72.792               | 0.459 | 98.688   | 0.8126 | 0.799519     |
| 90        | 108.612          | 0.908 | 53.784               | 0.248 | 110.256  | 0.9079 | 0.896153     |
| 100       | 119.916          | 1.000 | 17.592               | 0.157 | 121.608  | 1.0000 | 0.990462     |

| 4.1                                 | TABLE : Reactive power control |               |                   |                | P |
|-------------------------------------|--------------------------------|---------------|-------------------|----------------|---|
| 4.1 fixed displacement factor cos Ø |                                |               |                   |                |   |
| P (setting)                         | PF (setting)                   | P (measuring) | Q (max measuring) | PF (measuring) |   |
| P.F. setting 0.95 lagging           |                                |               |                   |                |   |
| 0% (1%)                             | 0.95 lagging                   | 5.69          | -1.90             | 0.9501         |   |
| 10%                                 | 0.95 lagging                   | 11.38         | -3.84             | 0.9500         |   |
| 20%                                 | 0.95 lagging                   | 22.82         | -7.42             | 0.9505         |   |
| 30%                                 | 0.95 lagging                   | 34.30         | -11.04            | 0.9504         |   |
| 40%                                 | 0.95 lagging                   | 45.48         | -15.50            | 0.9502         |   |
| 50%                                 | 0.95 lagging                   | 57.19         | -18.14            | 0.9505         |   |
| 60%                                 | 0.95 lagging                   | 68.40         | -22.58            | 0.9497         |   |
| 70%                                 | 0.95 lagging                   | 79.54         | -26.93            | 0.9499         |   |
| 80%                                 | 0.95 lagging                   | 91.49         | -29.11            | 0.9504         |   |
| 90%                                 | 0.95 lagging                   | 102.67        | -33.43            | 0.9506         |   |
| 100%                                | 0.95 lagging                   | 114.10        | -36.98            | 0.9507         |   |
| P.F. setting 0.95 leading           |                                |               |                   |                |   |
| 0% (1%)                             | 0.95 leading                   | 5.71          | 1.87              | 0.9504         |   |
| 10%                                 | 0.95 leading                   | 11.38         | 3.82              | 0.9502         |   |
| 20%                                 | 0.95 leading                   | 22.85         | 7.39              | 0.9504         |   |
| 30%                                 | 0.95 leading                   | 34.30         | 10.97             | 0.9505         |   |
| 40%                                 | 0.95 leading                   | 45.60         | 15.05             | 0.9498         |   |
| 50%                                 | 0.95 leading                   | 56.93         | 19.08             | 0.9500         |   |
| 60%                                 | 0.95 leading                   | 68.62         | 21.98             | 0.9506         |   |
| 70%                                 | 0.95 leading                   | 79.90         | 25.85             | 0.9510         |   |
| 80%                                 | 0.95 leading                   | 90.98         | 30.60             | 0.9496         |   |
| 90%                                 | 0.95 leading                   | 102.67        | 33.65             | 0.9506         |   |
| 100%                                | 0.95 leading                   | 114.22        | 36.91             | 0.9506         |   |
| P.F. setting 0.9 lagging            |                                |               |                   |                |   |
| 0% (1%)                             | 0.90 lagging                   | 5.39          | -2.61             | 0.9002         |   |
| 10%                                 | 0.90 lagging                   | 10.78         | -5.22             | 0.9001         |   |

|                          |              |        |        |        |
|--------------------------|--------------|--------|--------|--------|
| 20%                      | 0.90 lagging | 21.62  | -10.47 | 0.9006 |
| 30%                      | 0.90 lagging | 32.49  | -15.74 | 0.9005 |
| 40%                      | 0.90 lagging | 43.09  | -20.87 | 0.9003 |
| 50%                      | 0.90 lagging | 54.18  | -26.25 | 0.9006 |
| 60%                      | 0.90 lagging | 64.80  | -31.39 | 0.8998 |
| 70%                      | 0.90 lagging | 75.35  | -36.50 | 0.9000 |
| 80%                      | 0.90 lagging | 86.67  | -41.99 | 0.9005 |
| 90%                      | 0.90 lagging | 97.27  | -47.12 | 0.9007 |
| 100%                     | 0.90 lagging | 108.09 | -52.37 | 0.9008 |
| P.F. setting 0.9 leading |              |        |        |        |
| 0% (1%)                  | 0.90 leading | 5.41   | 2.62   | 0.9005 |
| 10%                      | 0.90 leading | 10.78  | 5.22   | 0.9003 |
| 20%                      | 0.90 leading | 21.65  | 10.49  | 0.9005 |
| 30%                      | 0.90 leading | 32.49  | 15.74  | 0.9006 |
| 40%                      | 0.90 leading | 43.20  | 20.93  | 0.8999 |
| 50%                      | 0.90 leading | 53.93  | 26.13  | 0.9001 |
| 60%                      | 0.90 leading | 65.01  | 31.49  | 0.9007 |
| 70%                      | 0.90 leading | 75.69  | 36.67  | 0.9011 |
| 80%                      | 0.90 leading | 86.19  | 41.76  | 0.8997 |
| 90%                      | 0.90 leading | 97.27  | 47.12  | 0.9007 |
| 100%                     | 0.90 leading | 108.21 | 52.42  | 0.9007 |
| P.F. setting PF 1.0      |              |        |        |        |
| 0% (1%)                  | 1.0          | 5.93   | -0.96  | 0.9887 |
| 10%                      | 1.0          | 11.90  | -1.54  | 0.9934 |
| 20%                      | 1.0          | 23.86  | -2.71  | 0.9936 |
| 30%                      | 1.0          | 35.81  | -3.60  | 0.9943 |
| 40%                      | 1.0          | 47.86  | -3.65  | 0.9975 |
| 50%                      | 1.0          | 59.83  | -4.06  | 0.9978 |
| 60%                      | 1.0          | 71.93  | -3.50  | 0.9990 |
| 70%                      | 1.0          | 83.93  | -3.48  | 0.9992 |
| 80%                      | 1.0          | 95.98  | -2.88  | 0.9997 |
| 90%                      | 1.0          | 108.00 | -2.09  | 0.9998 |
| 100%                     | 1.0          | 120.05 | -1.58  | 0.9999 |

| 5             | TABLE : Active power control |                      |                              | P         |  |
|---------------|------------------------------|----------------------|------------------------------|-----------|--|
| Power Setting |                              | Power Measuring [kW] | Power Deviation of set point |           |  |
| Power [%]     | Power [kW]                   |                      | Power [kW]                   | Power [%] |  |
| 100%          | 120.00                       | 120.02               | -0.01                        | -0.01     |  |
| 90%           | 108.00                       | 107.98               | 0.02                         | 0.02      |  |
| 80%           | 96.00                        | 95.98                | 0.03                         | 0.03      |  |
| 70%           | 84.00                        | 83.95                | 0.04                         | 0.05      |  |
| 60%           | 72.00                        | 71.90                | 0.05                         | 0.07      |  |
| 50%           | 60.00                        | 59.88                | 0.06                         | 0.10      |  |
| 40%           | 48.00                        | 47.78                | 0.10                         | 0.21      |  |
| 30%           | 36.00                        | 35.78                | 0.10                         | 0.28      |  |
| 20%           | 24.00                        | 23.81                | 0.08                         | 0.34      |  |
| 10%           | 12.00                        | 11.90                | 0.05                         | 0.42      |  |

Supplementary information:



| 6  | Low Voltage Fault Ride Through ( 90% Power )        |                     | P |
|--|---|---------------------|---|
| List of tests                                | Residual amplitude of phase-to-phase voltage V/Vnom | Duration Time (sec) |   |
| file:1-three-phase symmetrical faults        | 0.7-0.8 ( V1/Vnom)                                  | 1.520               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.161               |   |
|  | 0-0.049 (V3/Vnom)                                   | 0.162               |   |
| file:2-A-phase – B- phase symmetrical faults | 0.7-0.8 ( V1/Vnom)                                  | 1.522               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.162               |   |
|  | 0-0.049 (V3/Vnom)                                   | 0.162               |   |
| file:3-B-phase – C- phase symmetrical faults | 0.7-0.8 ( V1/Vnom)                                  | 1.527               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.162               |   |
|  | 0-0.049 (V3/Vnom)                                   | 0.162               |   |
| file:4-A-phase – C- phase symmetrical faults | 0.7-0.8 ( V1/Vnom)                                  | 1.522               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.161               |   |
|  | 0-0.049 (V3/Vnom)                                   | 0.161               |   |
| file:5- A-phase symmetrical faults           | 0.7-0.8 (V4/Vnom)                                   | 1.527               |   |
|  | 0.3-0.5 (V5/Vnom)                                   | 0.166               |   |
|  | 0-0.049 (V6/Vnom)                                   | 0.166               |   |
| file:6- B-phase symmetrical faults           | 0.7-0.8 (V7/Vnom)                                   | 1.527               |   |
|  | 0.3-0.5 (V8/Vnom)                                   | 0.162               |   |
|  | 0-0.049 (V9/Vnom)                                   | 0.162               |   |
| file:7- C-phase symmetrical faults           | 0.7-0.8 (V7/Vnom)                                   | 1.532               |   |
|  | 0.3-0.5 (V8/Vnom)                                   | 0.160               |   |
|  | 0-0.049 (V9/Vnom)                                   | 0.160               |   |
| Low Voltage Fault Ride Through ( 30% Power ) |   |                     |   |
| List of tests                                | Residual amplitude of phase-to-phase voltage V/Vnom | Duration Time (sec) |   |
| file:1-three-phase symmetrical faults        | 0.7-0.8 ( V1/Vnom)                                  | 1.532               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.160               |   |
|  | 0-0.049 (V3/Vnom)                                   | 0.160               |   |
| file:2-A-phase – B- phase symmetrical faults | 0.7-0.8 ( V1/Vnom)                                  | 1.522               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.161               |   |
|  | 0-0.049 (V3/Vnom)                                   | 0.162               |   |
| file:3-B-phase – C- phase symmetrical faults | 0.7-0.8 ( V1/Vnom)                                  | 1.527               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.161               |   |
|  | 0-0.049 (V3/Vnom)                                   | 0.162               |   |
| file:4-A-phase – C- phase symmetrical faults | 0.7-0.8 ( V1/Vnom)                                  | 1.527               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.162               |   |
|  | 0-0.049 (V3/Vnom)                                   | 0.161               |   |
| file:5- A-phase symmetrical faults           | 0.7-0.8 (V4/Vnom)                                   | 1.532               |   |
|  | 0.3-0.5 (V5/Vnom)                                   | 0.166               |   |
|  | 0-0.049 (V6/Vnom)                                   | 0.160               |   |
| file:6- B-phase symmetrical faults           | 0.7-0.8 (V7/Vnom)                                   | 1.527               |   |
|  | 0.3-0.5 (V8/Vnom)                                   | 0.161               |   |
|  | 0-0.049 (V9/Vnom)                                   | 0.162               |   |
| file:7- C-phase symmetrical faults           | 0.7-0.8 (V7/Vnom)                                   | 1.527               |   |
|  | 0.3-0.5 (V8/Vnom)                                   | 0.162               |   |
|  | 0-0.049 (V9/Vnom)                                   | 0.160               |   |
| Low Voltage Fault Ride Through ( 10% Power ) |   |                     |   |
| List of tests                                | Residual amplitude of phase-to-phase voltage V/Vnom | Duration Time (sec) |   |
| file:1-three-phase symmetrical faults        | 0.7-0.8 ( V1/Vnom)                                  | 1.507               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.162               |   |
|  | 0-0.049 (V3/Vnom)                                   | 0.160               |   |
| file:2-A-phase – B- phase symmetrical faults | 0.7-0.8 ( V1/Vnom)                                  | 1.506               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.161               |   |
|  | 0-0.049 (V3/Vnom)                                   | 0.162               |   |
| file:3-B-phase – C- phase symmetrical        | 0.7-0.8 ( V1/Vnom)                                  | 1.507               |   |
|  | 0.3-0.5 (V2/Vnom)                                   | 0.162               |   |


|  |                   |       |
|--|-------------------|-------|
| faults                                       | 0-0.049 (V3/Vnom) | 0.160 |
| file:4-A-phase – C- phase symmetrical faults | 0.7-0.8 (V1/Vnom) | 1.501 |
|  | 0.3-0.5 (V2/Vnom) | 0.161 |
| file:5- A-phase symmetrical faults           | 0-0.049 (V3/Vnom) | 0.161 |
|  | 0.7-0.8 (V4/Vnom) | 1.527 |
|  | 0.3-0.5 (V5/Vnom) | 0.167 |
| file:6- B-phase symmetrical faults           | 0-0.049 (V6/Vnom) | 0.166 |
|  | 0.7-0.8 (V7/Vnom) | 1.501 |
|  | 0.3-0.5 (V8/Vnom) | 0.161 |
| file:7- C-phase symmetrical faults           | 0-0.049 (V9/Vnom) | 0.161 |
|  | 0.7-0.8 (V7/Vnom) | 1.527 |
|  | 0.3-0.5 (V8/Vnom) | 0.160 |
|  | 0-0.049 (V9/Vnom) | 0.160 |

Supplementary information(90% Power):

|  |  |
|--|--|
|  |  |
| Three-phase faults 0.7-0.8 Vn                    | Three-phase faults 0.3-0.5 Vn                    |
|  |  |
| Three-phase faults 0-0.049 Vn                    | A-phase – B- phase symmetrical faults 0.7-0.8 Vn |
|  |  |
| A-phase – B- phase symmetrical faults 0.3-0.5 Vn | A-phase – B- phase symmetrical faults 0-0.049 Vn |

|   |   |
|---|---|
|   |   |
| <p>B-phase – C- phase symmetrical faults<br/>0.7-0.8 Vn</p> | <p>B-phase – C- phase symmetrical faults<br/>0.3-0.5 Vn</p> |
|   |   |
| <p>B-phase – C- phase symmetrical faults<br/>0-0.049 Vn</p> | <p>A-phase – C- phase symmetrical faults<br/>0.7-0.8 Vn</p> |
|   |   |
| <p>A-phase – C- phase symmetrical faults<br/>0.3-0.5 Vn</p> | <p>A-phase – C- phase symmetrical faults<br/>0-0.049 Vn</p> |
|   |   |
| <p>A-phase symmetrical faults 0.7-0.8 Vn</p>                | <p>A-phase symmetrical faults 0.3-0.5 Vn</p>                |






|   |  |
|---|--|
|   |  |
| <p>A-phase symmetrical faults 0-0.049 Vn</p>  | <p>B-phase symmetrical faults 0.7-0.8 Vn</p> |
|   |  |
| <p>B-phase symmetrical faults 0.3-0.5 Vn</p>  | <p>B-phase symmetrical faults 0-0.049 Vn</p> |
|   |  |
| <p>C-phase symmetrical faults 0.7-0.8 Vn</p>  | <p>C-phase symmetrical faults 0.3-0.5 Vn</p> |
|   | <p>--</p>                                    |
| <p>C- phase symmetrical faults 0-0.049 Vn</p> | <p>--</p>                                    |
| <p>Supplementary information(30% Power):</p>  |  |



|   |   |
|---|---|
|   |   |
| <p align="center"><b>B-phase – C- phase symmetrical faults<br/>0-0.049 Vn</b></p> | <p align="center"><b>A-phase – C- phase symmetrical faults<br/>0.7-0.8 Vn</b></p> |
|   |   |
| <p align="center"><b>A-phase – C- phase symmetrical faults<br/>0.3-0.5 Vn</b></p> | <p align="center"><b>A-phase – C- phase symmetrical faults<br/>0.7-0.8 Vn</b></p> |
|   |   |
| <p align="center"><b>A-phase symmetrical faults 0.7-0.8 Vn</b></p>                | <p align="center"><b>A-phase symmetrical faults 0.3-0.5 Vn</b></p>                |
|   |   |
| <p align="center"><b>A-phase symmetrical faults 0-0.049 Vn</b></p>                | <p align="center"><b>B-phase symmetrical faults 0.7-0.8 Vn</b></p>                |

|   |  |
|---|--|
|   |  |
| <p>B-phase symmetrical faults 0.3-0.5 Vn</p>  | <p>B-phase symmetrical faults 0-0.049 Vn</p> |
|   |  |
| <p>C-phase symmetrical faults 0.7-0.8 Vn</p>  | <p>C-phase symmetrical faults 0.3-0.5 Vn</p> |
|   | <p>--</p>                                    |
| <p>C- phase symmetrical faults 0-0.049 Vn</p> | <p>--</p>                                    |
| <p>Supplementary information(10% Power):</p>  |  |
|   |  |
| <p>Three-phase faults 0.7-0.8 Vn</p>          | <p>Three-phase faults 0.3-0.5 Vn</p>         |


|   |   |
|---|---|
|   |   |
| <p>Three-phase faults 0-0.049 Vn</p>                    | <p>A-phase – B- phase symmetrical faults 0.7-0.8 Vn</p> |
|   |   |
| <p>A-phase – B- phase symmetrical faults 0.3-0.5 Vn</p> | <p>A-phase – B- phase symmetrical faults 0-0.049 Vn</p> |
|   |   |
| <p>B-phase – C- phase symmetrical faults 0.7-0.8 Vn</p> | <p>B-phase – C- phase symmetrical faults 0.3-0.5 Vn</p> |
|   |   |
| <p>B-phase – C- phase symmetrical faults 0-0.049 Vn</p> | <p>A-phase – C- phase symmetrical faults 0.7-0.8 Vn</p> |


|   |  |
|---|--|
|    |    |
| <p>A-phase – C- phase symmetrical faults<br/>0.3-0.5 Vn</p>                         | <p>A-phase – C- phase symmetrical faults<br/>0-0.049 Vn</p>                          |
|    |    |
| <p>A-phase symmetrical faults 0.7-0.8 Vn</p>  | <p>A-phase symmetrical faults 0.3-0.5 Vn</p>   |
|  |  |
| <p>A-phase symmetrical faults 0-0.049 Vn</p>  | <p>B-phase symmetrical faults 0.7-0.8 Vn</p>   |
|  |  |
| <p>B-phase symmetrical faults 0.3-0.5 Vn</p>  | <p>B-phase symmetrical faults 0-0.049 Vn</p>   |

|   |  |
|---|--|
|   |  |
| <p>C-phase symmetrical faults 0.7-0.8 Vn</p>  | <p>C-phase symmetrical faults 0.3-0.5 Vn</p> |
|   | <p>--</p>                                    |
| <p>C- phase symmetrical faults 0-0.049 Vn</p> | <p>--</p>                                    |


| 7 TABLE: Operating Voltage Range |                   |                             |                  |                             |                        |                             | P      |   |
|----------------------------------|-------------------|-----------------------------|------------------|-----------------------------|------------------------|-----------------------------|--------|---|
| No.                              | Voltage Range (V) | Setting voltage (V)         | Setting time (s) | Test voltage (V)            | Disconnecting time (s) | Max. Disconnecting time (s) | Result |   |
| 1                                | V<50%             | L1 = L2 = L3 = 110V         | 0.1              | L1 = L2 = L3 = 109V         | 0.213                  | 0.3                         | P      |   |
|                                  |                   | L1 = 110 V, L2 = L3 = 220 V |                  | L1 = 109V, L2 = L3 = 220 V  |                        |                             | 0.217  | P |
|                                  |                   | L2 = 110V, L1 = L3 = 220 V  |                  | L2 = 109V, L1 = L3 = 220 V  |                        |                             | 0.223  | P |
|                                  |                   | L3 = 110 V, L1 = L2 = 220 V |                  | L3 = 109 V, L1 = L2 = 220 V |                        |                             | 0.207  | P |
| 2                                | 50% ≤ V < 90%     | L1 = L2 = L3 = 111 V        | 0.1              | L1 = L2 = L3 = 112 V        | 1.808                  | 2                           | P      |   |
|                                  |                   | L1 = 111 V, L2 = L3 = 220 V | 0.1              | L1 = 112 V, L2 = L3 = 220 V | 1.795                  | 2                           | P      |   |
|                                  |                   | L2 = 111 V, L1 = L3 = 220 V | 0.1              | L2 = 112 V, L1 = L3 = 220 V | 1.800                  | 2                           | P      |   |
|                                  |                   | L3 = 111 V, L1 = L2 = 220 V | 0.1              | L3 = 112 V, L1 = L2 = 220 V | 1.798                  | 2                           | P      |   |
|                                  |                   | L1 = L2 = L3 = 197 V        | 0.1              | L1 = L2 = L3 = 196 V        | 1.818                  | 2                           | P      |   |
|                                  |                   | L1 = 197 V, L2 = L3 = 220 V | 0.1              | L1 = 196 V, L2 = L3 = 220 V | 1.795                  | 2                           | P      |   |
|                                  |                   | L2 = 197 V, L1 =            | 0.1              | L2 = 196 V, L1 =            | 1.814                  | 2                           | P      |   |

|   |                 |                             |     |                             |          |          |   |
|---|-----------------|-----------------------------|-----|-----------------------------|----------|----------|---|
|   |                 | L3 = 220 V                  |     | = L3 = 220 V                |          |          |   |
|   |                 | L3 = 197 V, L1 = L2 = 220 V | 0.1 | L3 = 196 V, L1 = L2 = 220 V | 1.806    | 2        | P |
| 3 | 90% ≤ V ≤ 110%  | L1 = L2 = L3 = 197 V        | --  | L1 = L2 = L3 = 198 V        | CONTINUE | CONTINUE | P |
| 4 |                 | L1 = L2 = L3 = 241V         | --  | L1 = L2 = L3 = 240V         | CONTINUE | CONTINUE | P |
| 5 | 110% < V < 120% | L1 = L2 = L3 = 241V         | 0.1 | L1 = L2 = L3 = 242V         | 0.802    | 1        | P |
|   |                 | L1 = 241 V, L2 = L3 = 220 V | 0.1 | L1 = 242V, L2 = L3 = 220 V  | 0.797    | 1        | P |
|   |                 | L2 = 241 V, L1 = L3 = 220 V | 0.1 | L2 = 242 V, L1 = L3 = 220 V | 0.820    | 1        | P |
|   |                 | L3 = 241 V, L1 = L2 = 220 V | 0.1 | L3 = 242 V, L1 = L2 = 220 V | 0.820    | 1        | P |
|   |                 | L1 = L2 = L3 = 262V         | 0.1 | L1 = L2 = L3 = 261 V        | 0.804    | 1        | P |
|   |                 | L1 = 262 V, L2 = L3 = 220 V | 0.1 | L1 = 261V, L2 = L3 = 220 V  | 0.807    | 1        | P |
|   |                 | L2 = 262 V, L1 = L3 = 220 V | 0.1 | L2 = 261V, L1 = L3 = 220 V  | 0.799    | 1        | P |
|   |                 | L3 = 262 V, L1 = L2 = 220 V | 0.1 | L3 = 261 V, L1 = L2 = 220 V | 0.820    | 1        | P |
| 6 | V ≥ 120%        | L1 = L2 = L3 = 263V         | 0.1 | L1 = L2 = L3 = 264 V        | 0.100    | 0.16     | P |
|   |                 | L1 = 263 V, L2 = L3 = 220 V | 0.1 | L1 = 264 V, L2 = L3 = 220 V | 0.115    | 0.16     | P |
|   |                 | L2 = 263 V, L1 = L3 = 220 V | 0.1 | L2 = 264 V, L1 = L3 = 220 V | 0.120    | 0.16     | P |
|   |                 | L3 = 263 V, L1 = L2 = 220 V | 0.1 | L3 = 264 V, L1 = L2 = 220 V | 0.128    | 0.16     | P |







V < 50%, L1 = 109V, L2 = L3 = 220 V



V < 50%, L2 = 109V, L1 = L3 = 220 V



V < 50%, L3 = 109V, L1 = L2 = 220 V




50% ≤ V < 90%, L1 = L2 = L3 = 112 V




50% ≤ V < 90%, L1 = 112 V, L2 = L3 = 220 V



50% ≤ V < 90%, L2 = 112 V, L1 = L3 = 220 V




50% ≤ V < 90%, L3 = 112 V, L1 = L2 = 220 V



50% ≤ V < 90%, L1 = L2 = L3 = 196 V




50% ≤ V < 90%, L1 = 196 V, L2 = L3 = 220 V




50% ≤ V < 90%, L2 = 196 V, L1 = L3 = 220 V



50% ≤ V < 90%, L3 = 196 V, L1 = L2 = 220 V




90% ≤ V ≤ 110%, L1 = L2 = L3 = 198 V




$90\% \leq V \leq 110\%$ ,  $L1 = L2 = L3 = 240\text{ V}$



$110\% < V < 120\%$ ,  $L1 = L2 = L3 = 242\text{ V}$



$110\% < V < 120\%$ ,  $L1 = 242\text{ V}$ ,  $L2 = L3 = 220\text{ V}$




110%<V<120%, L2 = 242V, L1 = L3 = 220 V




110%<V<120%, L3 = 242V, L1 = L2 = 220 V



110%<V<120%, L1 = L2 = L3 = 261 V




110%<V<120%, L1 = 261 V, L2 = L3 = 220 V



110%<V<120%, L2 = 261 V, L1 = L3 = 220 V




110%<V<120%, L3 = 261 V, L1 = L2 = 220 V




$V \geq 120\%$ ,  $L1 = L2 = L3 = 264\text{ V}$



$V \geq 120\%$ ,  $L1 = 264\text{ V}$ ,  $L2 = L3 = 220\text{ V}$




$V \geq 120\%$ ,  $L2 = 264\text{ V}$ ,  $L1 = L3 = 220\text{ V}$




| 8 TABLE: Operating Frequency Range |                      |                        |                  |                     |                        |                             | P      |
|------------------------------------|----------------------|------------------------|------------------|---------------------|------------------------|-----------------------------|--------|
| N o.                               | Frequency Range (Hz) | Setting Frequency (Hz) | Setting time (s) | Test Frequency (Hz) | Disconnecting Time (S) | Max. Disconnecting Time (S) | Result |
| 1                                  | 99%UFT               | 46.9                   | 0.06             | 46.9                | 0.0930                 | 0.1                         | P      |
| 2                                  | 110%UFT              | 47.1                   | --               | 47.1                | Cont.                  | Cont.                       | P      |
| 3                                  | 90%OFT               | 51.9                   | --               | 51.9                | Cont.                  | Cont.                       | P      |
| 4                                  | 101%OFT              | 52.1                   | 0.06             | 52.1                | 0.0915                 | 0.1                         | P      |


Supplementary information:  
 OFT: Over frequency Trip Setting  
 UFT: Under frequency Trip Setting  
 Cont.: Continuous operated




Under frequency < 46.9 Hz



Over frequency > 52.1 Hz



Frequency = 47.1 Hz



Frequency = 51.9 Hz

| 9  | TABLE: Islanding protection (EUT output = 100%) |  |  |                                |                        |                           |              |          | P            |
|--|---|--|--|--------------------------------|------------------------|---------------------------|--------------|----------|--------------|
| Test conditions                              |   |  | Frequency: 50+/-0.1Hz<br>UN=230+/-3Vac<br>Distortion factor of chokes < 2%<br>Quality =1 |                                |                        |                           |              |          |              |
| Disconnection limit                          |   |  | 2s for PEA   |                                |                        |                           |              |          |              |
| No   | 1)<br>PEUT<br>(% of EUT<br>rating)              | Reactive<br>load (% of<br>QL in<br>6.1.d) 1) | 2)<br>PAC<br>(% of<br>nominal)   | 3)<br>QAC<br>(% of<br>nominal) | Run on<br>Time<br>(ms) | PEUT<br>(kW per<br>phase) | Actual<br>Qf | V<br>(V) | Remarks4)    |
| 1  | 100   | 100  | 0  | 0                              | 196                    | 39.891                    | 0.998        | 818      | Test A at BL |
| 2  | 100   | 100  | -5   | -5                             | 160                    | 39.891                    | 1.021        | 818      | Test A at IB |
| 3  | 100   | 100  | -5   | 0                              | 159                    | 39.891                    | 1.039        | 818      | Test A at IB |
| 4  | 100   | 100  | -5   | +5                             | 138                    | 39.891                    | 1.081        | 818      | Test A at IB |
| 5  | 100   | 100  | 0  | -5                             | 134                    | 39.891                    | 0.972        | 818      | Test A at IB |
| 6  | 100   | 100  | 0  | +5                             | 168                    | 39.891                    | 1.020        | 818      | Test A at IB |
| 7  | 100   | 100  | +5   | -5                             | 159                    | 39.891                    | 0.928        | 818      | Test A at IB |
| 8  | 100   | 100  | +5   | 0                              | 157                    | 39.891                    | 0.957        | 818      | Test A at IB |
| 9  | 100   | 100  | +5   | +5                             | 157                    | 39.891                    | 0.964        | 818      | Test A at IB |
| 10   | 100   | 100  | -10  | +10                            | 168                    | 39.891                    | 0.998        | 818      | Test A at BL |
| 11   | 100   | 100  | -5   | +10                            | 134                    | 39.891                    | 1.021        | 818      | Test A at IB |
| 12   | 100   | 100  | 0  | +10                            | 168                    | 39.891                    | 1.039        | 818      | Test A at IB |
| 13   | 100   | 100  | +5   | +10                            | 159                    | 39.891                    | 1.081        | 818      | Test A at IB |
| 14   | 100   | 100  | +10  | +10                            | 157                    | 39.891                    | 0.972        | 818      | Test A at IB |
| 15   | 100   | 100  | -10  | +5                             | 157                    | 39.891                    | 1.020        | 818      | Test A at IB |
| 16   | 100   | 100  | +10  | +5                             | 168                    | 39.891                    | 0.928        | 818      | Test A at IB |
| 17   | 100   | 100  | -10  | 0                              | 157                    | 39.891                    | 0.957        | 818      | Test A at IB |
| 18   | 100   | 100  | +10  | 0                              | 157                    | 39.891                    | 0.964        | 818      | Test A at IB |
| 19   | 100   | 100  | -10  | -5                             | 168                    | 39.891                    | 1.081        | 818      | Test A at IB |
| 20   | 100   | 100  | +10  | -5                             | 134                    | 39.891                    | 0.972        | 818      | Test A at IB |
| 21   | 100   | 100  | -10  | -10                            | 168                    | 39.891                    | 1.020        | 818      | Test A at IB |
| 22   | 100   | 100  | -5   | -10                            | 159                    | 39.891                    | 0.928        | 818      | Test A at IB |
| 23   | 100   | 100  | 0  | -10                            | 168                    | 39.891                    | 0.957        | 818      | Test A at IB |
| 24   | 100   | 100  | +5   | -10                            | 147                    | 39.891                    | 0.964        | 818      | Test A at IB |
| 25   | 100   | 100  | -10  | -10                            | 153                    | 39.891                    | 0.964        | 818      | Test A at IB |
| Parameter at 0% per phase                    |   |  | L= 51.49 mH  |                                | R= 17.32 Ω             |                           | C= 189.73 μF |          |              |
| IAC fundamental current at balance condition |   |  | L1: 71 mA  |                                | L2: 89 mA              |                           | L3: 71 mA    |          |              |

**Note:**

RLC is adjusted to min. +/-1% of the inverter rated output power

- 1) PEUT: EUT output power
- 2) PAC: Real power flow at S1 in Figure 1. Positive means power from EUT to utility. Nominal is the 0 % test condition value.
- 3) QAC: Reactive power flow at S1 in Figure 1. Positive means power from EUT to utility. Nominal is the 0 % test condition value.
- 4) BL: Balance condition, IB: Imbalance condition.


**Condition A:**

EUT output power PEUT = Maximum5)

EUT input voltage 6) = 100% of rated input voltage range

- 5) Maximum EUT output power condition should be achieved using the maximum allowable input power. Actual output power may exceed nominal rated output.
- 6) Based on EUT rated input operating range. For example, If range is between X volts and Y volts, 90 % of range =  $X + 0.9 \times (Y - X)$ . Y shall not exceed  $0.8 \times$  EUT maximum system voltage (i.e., maximum allowable array open circuit voltage). In any case, the EUT should not be operated outside of its allowable input voltage range.

**Disconnection at P<sub>AC</sub> 0% and Q<sub>AC</sub> 0% reactive load No. 6**



**Attention:**

**For Thailand only picture with all three current phases L1, L2 and L3 are accepted**


All relays are direct coupled and open directly by receiving the islanding signal from the controller.

**Note:**

CH1, CH2, CH3: L1, L2, L3 current of EUT(8A/div); CH4, CH5, CH6: L1, L2, L3 I<sub>AC</sub>(2A/div).

|                 |  |          |
|-----------------|--|----------|
| <b>9</b>        | <b>TABLE: Islanding protection (EUT output = 66%)</b>                                    | <b>P</b> |
| Test conditions | Frequency: 50+/-0.1Hz<br>UN=230+/-3Vac<br>Distortion factor of chokes < 2%<br>Quality =1 |          |

| Disconnection limit   |                                    |  | 2s for PEA                     |                                |                        |                           |              |          |                       |
|---|------------------------------------|--|--------------------------------|--------------------------------|------------------------|---------------------------|--------------|----------|-----------------------|
| No  | 1)<br>PEUT<br>(% of EUT<br>rating) | Reactive<br>load (% of<br>QL in<br>6.1.d) 1) | 2)<br>PAC<br>(% of<br>nominal) | 3)<br>QAC<br>(% of<br>nominal) | Run on<br>Time<br>(ms) | PEUT<br>(kW per<br>phase) | Actual<br>Qf | V<br>(V) | Remarks <sup>4)</sup> |
| 1   | 66                                 | 66   | 0                              | -5                             | 216                    | 26.628                    | 0.985        | 700      | Test B at IB          |
| 2   | 66                                 | 66   | 0                              | -4                             | 180                    | 26.628                    | 0.987        | 700      | Test B at IB          |
| 3   | 66                                 | 66   | 0                              | -3                             | 183                    | 26.628                    | 0.981        | 700      | Test B at IB          |
| 4   | 66                                 | 66   | 0                              | -2                             | 183                    | 26.628                    | 0.995        | 700      | Test B at IB          |
| 5   | 66                                 | 66   | 0                              | -1                             | 155                    | 26.628                    | 0.998        | 700      | Test B at IB          |
| 6   | 66                                 | 66   | 0                              | 0                              | 196                    | 26.628                    | 1.001        | 700      | Test B at BL          |
| 7   | 66                                 | 66   | 0                              | 1                              | 173                    | 26.628                    | 1.009        | 700      | Test B at IB          |
| 8   | 66                                 | 66   | 0                              | 2                              | 167                    | 26.628                    | 1.012        | 700      | Test B at IB          |
| 9   | 66                                 | 66   | 0                              | 3                              | 165                    | 26.628                    | 1.017        | 700      | Test B at IB          |
| 10  | 66                                 | 66   | 0                              | 4                              | 162                    | 26.628                    | 1.022        | 700      | Test B at IB          |
| 11  | 66                                 | 66   | 0                              | 5                              | 159                    | 26.628                    | 1.027        | 700      | Test B at IB          |
| Parameter at 0% per phase   |                                    |  | L= 78.43 mH                    |                                | R= 24.39 Ω             |                           | C= 117.08 μF |          |                       |
| IAC fundamental current at balance condition  |                                    |  | L1: 16 mA                      |                                | L2: 39 mA              |                           | L3: 41 mA    |          |                       |
| <p><b>Note:</b><br/>           RLC is adjusted to min. +/-1% of the inverter rated output power<br/>           1) PEUT: EUT output power<br/>           2) PAC: Real power flow at S1 in Figure 1. Positive means power from EUT to utility. Nominal is the 0 % test condition value.<br/>           3) QAC: Reactive power flow at S1 in Figure 1. Positive means power from EUT to utility. Nominal is the 0 % test condition value.<br/>           4) BL: Balance condition, IB: Imbalance condition.<br/>           Condition A:<br/>           EUT output power PEUT = Maximum 5)<br/>           EUT input voltage 6) = 66% of rated input voltage range<br/>           5) Maximum EUT output power condition should be achieved using the maximum allowable input power. Actual output power may exceed nominal rated output.<br/>           6) Based on EUT rated input operating range. For example, If range is between X volts and Y volts, 90 % of range =X + 0.9 × (Y – X). Y shall not exceed 0.8 × EUT maximum system voltage (i.e., maximum allowable array open circuit voltage). In any case, the EUT should not be operated outside of its allowable input voltage range.</p> |                                    |  |                                |                                |                        |                           |              |          |                       |



**Attention:**

**For Thailand only picture with all three current phases L1, L2 and L3 are accepted**

All relays are direct coupled and open directly by receiving the islanding signal from the controller.

**Note:**

CH1, CH2, CH3: L1, L2, L3 current of EUT(8A/div); CH4, CH5, CH6: L1, L2, L3 I<sub>AC</sub>(0.8A/div).

| 9 TABLE: Islanding protection (EUT output = 33%) |                           |                                     |  |                       |                  |                     |           |       | P            |
|--|---------------------------|-------------------------------------|--|-----------------------|------------------|---------------------|-----------|-------|--------------|
| Test conditions                                  |                           |                                     | Frequency: 50+/-0.1Hz<br>UN=220+/-3Vac<br>Distortion factor of chokes < 2%<br>Quality =1 |                       |                  |                     |           |       |              |
| Disconnection limit                              |                           |                                     | 2s for PEA   |                       |                  |                     |           |       |              |
| No   | 1) PEUT (% of EUT rating) | Reactive load (% of QL in 6.1.d) 1) | 2) PAC (% of nominal)  | 3) QAC (% of nominal) | Run on Time (ms) | PEUT (kW per phase) | Actual Qf | V (V) | Remarks4)    |
| 1  | 33                        | 33                                  | 0  | -5                    | 221              | 13.227              | 0.977     | 590   | Test C at IB |
| 2  | 33                        | 33                                  | 0  | -4                    | 175              | 13.227              | 0.983     | 590   | Test C at IB |
| 3  | 33                        | 33                                  | 0  | -3                    | 161              | 13.227              | 0.987     | 590   | Test C at IB |
| 4  | 33                        | 33                                  | 0  | -2                    | 176              | 13.227              | 0.992     | 590   | Test C at IB |
| 5  | 33                        | 33                                  | 0  | -1                    | 174              | 13.227              | 0.998     | 590   | Test C at IB |
| 6  | 33                        | 33                                  | 0  | 0                     | 173              | 13.227              | 1.003     | 590   | Test C at BL |
| 7  | 33                        | 33                                  | 0  | 1                     | 165              | 13.227              | 1.006     | 590   | Test C at IB |
| 8  | 33                        | 33                                  | 0  | 2                     | 112              | 13.227              | 1.011     | 590   | Test C at IB |
| 9  | 33                        | 33                                  | 0  | 3                     | 188              | 13.227              | 1.016     | 590   | Test C at IB |

|  |    |    |              |   |            |        |             |     |              |
|--|----|----|--------------|---|------------|--------|-------------|-----|--------------|
| 10   | 33 | 33 | 0            | 4 | 157        | 13.227 | 1.021       | 590 | Test C at IB |
| 11   | 33 | 33 | 0            | 5 | 146        | 13.227 | 1.026       | 590 | Test C at IB |
| Parameter at 0% per phase                    |    |    | L= 150.33 mH |   | R= 48.27 Ω |        | C= 65.49 μF |     |              |
| IAC fundamental current at balance condition |    |    | L1: 42 mA    |   | L2: 54 mA  |        | L3: 44 mA   |     |              |

**Note:**

RLC is adjusted to min. +/-1% of the inverter rated output power

- 1) PEUT: EUT output power
- 2) PAC: Real power flow at S1 in Figure 1. Positive means power from EUT to utility. Nominal is the 0 % test condition value.
- 3) QAC: Reactive power flow at S1 in Figure 1. Positive means power from EUT to utility. Nominal is the 0 % test condition value.
- 4) BL: Balance condition, IB: Imbalance condition.

**Condition A:**


EUT output power PEUT = Maximum 5)

EUT input voltage 6) = 33% of rated input voltage range

5) Maximum EUT output power condition should be achieved using the maximum allowable input power. Actual output power may exceed nominal rated output.

6) Based on EUT rated input operating range. For example, If range is between X volts and Y volts, 90 % of range =X + 0.9 × (Y – X). Y shall not exceed 0.8 × EUT maximum system voltage (i.e., maximum allowable array open circuit voltage). In any case, the EUT should not be operated outside of its allowable input voltage range.

**Disconnection at P<sub>AC</sub> 0% and Q<sub>AC</sub> 0% reactive load No. 6**



**Attention:**

**For Thailand only picture with all three current phases L1. L2 and L3 are accepted**

All relays are direct coupled and open directly by receiving the islanding signal from the controller.

**Note:**

CH1. CH2. CH3: L1. L2. L3 current of EUT(2A/div); CH4. CH5. CH6: L1. L2. L3 I<sub>AC</sub>(0.8A/div).

| Table: Response to Utility recovery test |             |                      |                   | P      |
|--|-------------|----------------------|-------------------|--------|
| Test condition                           | Limit (sec) | Actual Setting (sec) | Test Result (sec) | Result |
| Under frequency (46.9Hz)                 | 20 - 300    | 27                   | 228               | P      |
| Over frequency (52.1 Hz)                 |             | 27                   | 225               | P      |
| Under voltage level 1 (355 V)            |             | 27                   | 222               | P      |
| Over voltage level 1 (443 V)             |             | 27                   | 220               | P      |
| Under voltage level 2 (200 V)            |             | 27                   | 223               | P      |
| Over voltage level 2 (478 V)             |             | 27                   | 222               | P      |

Supplementary




Response to utility recovery over voltage level 1



Response to utility recovery under voltage level 1




Response to utility recovery over voltage level 2



Response to utility recovery under voltage level 2



Response to utility recovery under Frequency



Response to utility recovery over Frequency

Annex I  
 Equipment of test

| Equipment name            | Trade name     | Model        | S/N       | Cal. Due. Date |
|---------------------------|----------------|--------------|-----------|----------------|
| Power Analyzer            | YOKOGAVA       | WT3000       | EP-011    | 2020/09/24     |
| Programmable Power supply | DC<br>ATESS    | DC1000       | RD.02.100 | --             |
| Programmable Source       | AC<br>ATESS    | AC1000       | RD.02.101 | --             |
| Programmable Power supply | DC<br>Kewell   | TVS-630kW    | EP-027    | --             |
| Programmable Source       | AC<br>APC      | AFG-S-33800  | EP-026    | --             |
| Programmable Load         | RLC<br>Qunling | ACLT-38160H  | EP-028    | --             |
| Digital oscilloscope      | YOKOGAVA       | DL850        | EP-001    | 2020/09/05     |
| Differential probe        | CYBERTEK       | VP5200       | EP-003    | 2020/09/05     |
| Current probe             | YOKOGAVA       | CT-1000      | EP-012    | 2020/09/24     |
| Current probe             | YOKOGAVA       | CT-1000      | EP-013    | 2020/09/24     |
| Current probe             | YOKOGAVA       | CT-1000      | EP-014    | 2020/09/24     |
| Three phase impedance     | Teseq          | CCN 1000-3   | EE206-1   | 2020/08/23     |
| Signal conditioning Unit  | Teseq/Germany  | INA2197/37A  | EE206-2   | N/A            |
| Three phase impedance     | Teseq/Germany  | INA 2196/75A | EE206-3   | N/A            |

Annex II  
Specification of Inverter

Annex IV  
Laboratory Accreditation Certificate



Finger 3 Laboratory Accreditation Certificate