

# Accessories



Model	NOVO EVA-07/09/12S-PU
Mounting pole	
Dimension (W/H/D)	255/1500/154mm
Weight	11kg



Model	EVD-40SU	EVD-40DU
Mounting pole		
Dimension (W/H/D)	500/1652/300mm	
Weight	31kg	



Model	CARD WRITER
Contactless IC card	Supports Mifare 1 cards, TypeA CPU cards, and TypeB CPU cards that comply with the ISO14443 standard widely applied in the market.
Standard	RF interface that complies with ISO/IEC14443 TypeA and TypeB standard
Working frequency	13.56 MHz
Perating temperature	-20°C ~ 65°C;
Storage temperature	-20°C ~ 70°C;
Relative humidity	20-90%
Protection	TypeA CPU cards and TypeB CPU cards (embedded with CPU chips) for better encryption and security



Model	Multi-charge manager		
Specification			
System capacity	103.5KW	172.5KW	414KW
Normal input voltage/ range	400Vac 320~480Vac		
Normal input frequency/ range	50/60Hz 45-55Hz/55-65Hz		
Max. detection current	150A	250A	600A
Charger max. connection number	32PCS		
Max. communication distance	RS485 shielded twisted pair cable : 500m Ethernet cable : 100m		
Dimensions(W/H/D)	364*335*145mm		
Weight	6.5KG		
Operating temperature	-20°C~+50°C		
Protection degree	IP 65		
Relative humidity	0~95%		
Certification	CE		