


# Accessories



Model	NOVO EVA-07/11/22S-S/P	NOVO EVA-07/11/22D-SEW/PEW
Mounting pole		
Dimension (W/H/D)	255/1500/154mm	360/906.5/250mm
Weight	11kg	10kg



Model	EVD-20S	EVD-80D
Mounting pole		
Dimension (W/H/D)	360/1500/260mm	500/1652/300mm
Weight	14kg	31kg



Model	EVD-40S	EVD-40D
Mounting pole		
Dimension (W/H/D)	500/1652/300mm	
Weight	30kg	



Model	CARD WRITER
Contactless IC card	Supports Mifare 1 cards, TypeA CPU cards, and TypeB CPU cards that comply with the ISO14443 standard widely applied in the market.
Standard	RF interface that complies with ISO/IEC14443 TypeA and TypeB standard
Working frequency	13.56 MHz
Perating temperature	-20°C ~ 65°C;
Storage temperature	-20°C ~ 70°C;
Relative humidity	20-90%
Protection	TypeA CPU cards and TypeB CPU cards (embedded with CPU chips) for better encryption and security



Model	Multi-charge manager
Specification	
System capacity	692.8KW
Normal input voltage/ range	400Vac 320~480Vac
Normal input frequency/ range	50/60Hz 45-55Hz/55-65Hz
Max. detection current	1000A
Charger max. connection number	32PCS
Max. communication distance	RS485 shielded twisted pair cable : 500m Ethernet cable : 100m
Dimensions(W/H/D)	364*335*145mm
Weight	6.5KG
Operating temperature	-20°C~+50°C
Protection degree	IP 65
Relative humidity	0~95%
Certification	CE