

NOVO EVA-07/11/22D-SEW

NOVO EVA-07/11/22D-PEW

Floor/wall-mounting type AC EV charging station,
plug or socket type optional, dual output.



Features

-  Programmable charging mode
-  Comprehensive protection
-  Multiple communication modes
-  Dual output ports
-  EU standard
-  Flexible installation

Model	NOVO EVA-07D-SEW/PEW	NOVO EVA-11D-SEW/PEW	NOVO EVA-22D-SEW/PEW
Input & Output			
Input voltage	230V AC	400V AC	400V AC
Input frequency		50Hz/60Hz	
Output voltage	230V AC	400V AC	400V AC
Max.output power	7kW*2	11kW*2	22kW*2
Max.output current	32A*2	16A*2	32A*2
Charging interface type		IEC62196-2,Type2	
Connection		Socket/ Plug (opt)	
Cable Length		5m	
Number of connection		2	
Protection			
Over voltage protection		Yes	
Under voltage protection		Yes	
Over current protection		Yes	
Over load protection		Yes	
Short circuit protection		Yes	
Earth leakage protection		TypeA 30mA+6mA DC Fault current protection	
PEN protection(Pro-earth version)		Yes	
Over-temp protection		Yes	
Lightning protection		Yes	
Function & Accessory			
Ethernet/WIFI/4G		Yes/Yes/Opt	
LCD		Opt	
Charging Mode		APP/RFID/Plug and charge	
LED Indicator Light		Yes	
Intelligent power adjustment		Yes	
PV linkage		Yes	
Installation		Floor/wall-mounting	
Pro-earth		Opt	
MID meter		Opt	
OCP		1.6JSON	
Working Environment			
Ingress Protection		IP55/ IP65	
Operating temperature		-25°C ~+50°C	
Relative humidity		5-95% non-condensing	
Maximum altitude		2000m	
Cooling		Natural air cooling	
Standby power consumption		<8W	
Mechanical			
Dimension (W/H/D)		360/562/177mm	
Weight	< 14kg(Socket)	< 17kg(Socket)	< 17kg(Socket)
	< 18kg(Plug)	< 19kg(Plug)	< 20kg(Plug)
Certificate			
		CE RCM CB	