

# EVD-80/120/160/200D-X

Large capacity fast DC EV charging station for public use, double CCS plugs with automatic power adjustment between 2 plugs.



## Features

 Programmable charging mode

 Comprehensive protection

 Multiple communication modes

 POS payment terminal  
\*Reserved installation space and power supply provided.

 7 inch touch screen

 EU standard

 Dual output ports

Model	EVD-80D-X	EVD-120D-X	EVD-160D-X	EVD-200D-X
<b>Input &amp; Output</b>				
Input voltage range	320~457V AC			
Rated input voltage	AC400V(3P/N/PE)			
Rated input current	AC125A	AC185A	AC245A	AC305A
Rated frequency	50Hz			
DC plug type	CCS Type2, double plugs			
Output voltage range	CCS: DC150-1000V			
Rated power	80kW	120kW	160kW	200kW
Max. output current	CCS: DC200A			
Voltage-regulating accuracy	≤±0.5%			
Current-regulating accuracy	≤±1%			
Ripple coefficient	RMS: ≤±0.5%; Peak: ≤±1%			
Metering accuracy	Class 0.5			
Efficiency	>95%			
Cable Length	5m			
<b>Protection</b>				
Over voltage protection	Yes			
Under voltage protection	Yes			
Over current protection	Yes			
Over load protection	Yes			
Short circuit protection	Yes			
Earth leakage protection	Yes			
Emergency protection	Yes			
Over-temp protection	Yes			
Lightning protection	Yes			
<b>Function &amp; Accessory</b>				
Display	7 inch touch screen			
Ethernet/WIFI/4G	Yes/Yes/Opt			
Charging mode	APP/RFID/Plug and Charge/VIN			
Intelligent power adjustment	Yes			
Indicator	Yes			
Emergency stop	Yes			
Installation	Floor			
OCPP	1.6JSON			
<b>Working Environment</b>				
Ingress Protection	IP54			
Operating temperature	-25°C ~+50°C			
Relative humidity	5-95% non-condensing			
Maximum altitude	2000m			
Cooling	Forced air cooling			
Standby power consumption	<100W	<120W	<120W	<135W
Noise emission	≤65db			
<b>Mechanical</b>				
Dimension (W/H/D)	600/1883/803mm			
Weight	260kg	275kg	289kg	310kg
<b>Certificate</b>				
CE				