

MatrixOne IC261-US-208S

Outdoor All-in-one 125kW, 261kWh BESS cabinet with IP66/IP55 protection level, inbuilt PCS and liquid-cooling lithium-ion battery. Suitable for factory, industrial park, office, malls etc. to do peak-shaving and load-shifting. Integrated STS, can achieve on/off grid switch within 10ms.

Features

-  Parallel up to 10 units
-  Comprehensive protection
-  Built-in STS
-  IP66/IP55 protection
-  100% three-phase unbalanced load
-  AI-driven revenue optimization
-  All-in-one BESS cabinet
-  Distributed PV integration solution
-  Liquid-cooling battery ensure long lifespan



MatrixOne IC261-US-208S**Battery specification**

Cell type	LFP/314
Pack configuration	52.2kWh/IP52S
System configuration	261kWh/1P260S
Rated capacity	314Ah
Rated voltage	832V
Voltage range	728~936V
Rated charge/discharge	157A(0.5C)

PCS specification (on-grid)

Apparent power	125kVA
Rated power	125kW
Rated voltage	120/208Vac, 127/220Vac
Rated current	347A
Voltage range	102-148Vac/190-242Vac
Rated frequency	50/60Hz
Frequency range	45~55/55~65Hz
THDI	<3%
PF	0.8 lagging~0.8 leading
AC connection	3L/N/PE
Max. AC input power	187.5kW

PCS specification (off-grid)

Apparent power	125kVA
Rated power	125kW
Rated voltage	208V
Rated current	347A
THDU	≤2% linear
Rated frequency	50/60Hz
Overload capability	1.1times (long-term) 1.2times (10min)

General information

Dimensions (W*D*H)	1050*1350*2400 mm
Weight	2780kg
Max. round trip efficiency	92%
Cycle life	≥8000 cycles
Communication	MODBUS TCP/IP or RTU
HMI	Optional
Fire suppression system	Aerosol
Ingress rating	IP66(Battery Compartment)/ IP55
Cooling	Liquid cooling for battery + Forced air cooling for PCS
Operating temperature	-25°C~55°C (Derating after 45°C)
Anti-corrosion rating	C4 (C5 optional)
Humidity	0~95% RH (non-condensing)
Noise	≤75 dB
Altitude	3000m (Derating above 2000m)